



EUDEMON

CATÁLOGO - 2020



UF118



Size	Approved Rim	PR	LBS		PSI		Load Index		Tread Depth (mm)	Speed Rating (MPH)	Outside Diameter (in)	Section Width (in)
			S	D	S	D	S	D				
215/75R17.5	6.00	16	4805	4540	125	125	135	133	12.7	75	30.2	8.3
235/75R17.5	6.75	16	4410	4190	120	120	132	130	12.7	81	31.4	9.2
11R22.5	8.25	14	6175	5840	105	105	144	142	16.6	75	41.5	11.0
11R22.5	8.25	16	6945	6395	120	120	148	145	16.6	75	41.5	11.0
*275/80R22.5	8.25	16	7160	6610	120	120	146	143	16.6	75	40.2	11.1
295/75R22.5	9.00	14	6175	5675	110	110	144	141	16.6	75	39.9	11.7
295/75R22.5	9.00	16	6610	6005	120	120	146	143	16.6	75	39.9	11.7
11R24.5	8.25	14	6610	6005	105	105	146	143	16.6	75	43.5	11.0
11R24.5	8.25	16	7160	6610	120	120	149	146	16.6	75	43.5	11.0
285/75R24.5	8.25	14	6175	5675	110	110	144	141	16.6	75	41.3	11.1
285/75R24.5	8.25	16	6610	6005	120	120	147	144	16.6	75	41.3	11.1





UD120



POR CUALQUIER DEFECTO DE FABRICACIÓN

Size	Approved Rim	PR	LBS		PSI		Load Index		Tread Depth (mm)	Speed Rating (MPH)	Outside Diameter (in)	Section Width (in)
			S	D	S	D	S	D				
11R22.5	8.25	14	6175	5840	105	105	144	142	23.8	75	41.9	11.0
11R22.5	8.25	16	6945	6395	120	120	148	145	23.8	75	41.9	11.0
295/75R22.5	9.00	14	6175	5675	110	110	144	141	23.8	75	39.9	11.7
295/75R22.5	9.00	16	6610	6005	120	120	146	143	23.8	75	39.9	11.7
11R24.5	8.25	14	6610	6005	105	105	146	143	23.8	75	43.5	11.0
11R24.5	8.25	16	7160	6610	120	120	149	146	23.8	75	43.5	11.0
285/75R24.5	8.25	14	6175	5675	110	110	144	141	23.8	75	41.3	11.1
285/75R24.5	8.25	16	6610	6005	120	120	147	144	23.8	75	41.3	11.1





UU100



POR CUALQUIER DEFECTO DE FABRICACIÓN

Size	Approved Rim	PR	LBS		PSI		Load Index		Tread Depth (mm)	Speed Index	Driving Surface (mm)
			S	D	S	D	S	D			
11R22.5	8.25	16	6395	6395	120	120	148	145	20	J	220





UA235



Size	Approved Rim	PR	LBS		PSI		Load Index		Tread Depth (mm)	Speed Rating (MPH)	Ouside Diameter (In)	Section Width (In)
			S	D	S	D	S	D				
11R22.5	8.25	16	6610	6005	120	120	146	143	18	68	41.5	11.0
11R24.5	8.25	16	7160	6610	120	120	149	143	17.5	68	43.5	11.0

Tire Direct 
La nueva generación



TIRE DIRECT



/TIRE_DIRECT



/TIREDIRECTMX



TIRE DIRECT