

GREEN MAX



Tire Direct
La nueva generación



PCR TIRE CATALOGUE

Tire Direct
La nueva generación



www.tiredirect.com.mx


GREEN MAX

TABLE OF CONTENTS

8	<i>OPTIMUM UHP</i>	18	<i>OPTIMUM SPORT A/T</i>
10	<i>OPTIMUM HP</i>	20	<i>OPTIMUM X/T</i>
14	<i>OPTIMUM SPORT HP</i>	24	<i>EARTH TRAXX R/T</i>
16	<i>OPTIMUM SPORT H/T</i>	26	<i>OPTIMUM SPORT M/T</i>



OPTIMUM UHP



OPTIMUM HP



**OPTIMUM SPORT
HP**



**OPTIMUM SPORT
H/T**



**OPTIMUM SPORT
A/T**



OPTIMUM X/T



EARTH TRAXX R/T



**OPTIMUM SPORT
M/T**

COMPANY PROFILE





OPTIMUM SPORT M/T
MUD-TERRAIN

2025
NEW



EARTH TRAXX R/T
RUGGED-TERRAIN



OPTIMUM X/T
EXTREME ALL-TERRAIN



OPTIMUM SPORT HP
SUV ULTRA HIGH PERFORMANCE



OPTIMUM UHP
PCR ULTRA HIGH PERFORMANCE

Off Road



OPTIMUM SPORT A/T
ALL-TERRAIN



OPTIMUM SPORT H/T
HIGHWAY-TERRAIN



OPTIMUM HP
PCR HIGH PERFORMANCE

On Road

Sport

Comfort

ALL SEASON
ALL WEATHER

PASSENGER CAR TIRE




**OPTIMUM
UHP**



**OPTIMUM
HP**

GREEN MAX OPTIMUM UHP

PCR Ultra High Performance



- > Excellent steering & Handling performance
- > Outstanding wet road performance

Mileage Warranty: 50,000 Miles



- 1 Continuous central ribs-Enhance the stiffness of the central pattern blocks, improving steering performance.
- 2 Big shoulder block-The shoulder block delivers more rubber-to-road contact, increases the grip and steering feedback for better handling performance.
- 3 High turn-up carcass enhanced the handling. Also providing the safety guarantee.
- 4 Unique Z-shaped tread pattern design cuts into the water film effectively to reduce the risk of aquaplaning.
- 5 Full depth notches along with angled siping ensures effective water displacement management to enhance drainage speed for better performance in wet conditions.



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16	195/45R16 XL		84	V	61/2J	500	1102	340	50
	205/50R16 XL		91	W	61/2J	615	1356	340	50
	205/55R16 XL		94	W	61/2J	670	1477	340	50
	215/55R16 XL		97	W	7J	730	1609	340	50
	225/50R16 XL		96	V	7J	710	1565	340	50
	205/40R17 XL		84	W	71/2J	500	1102	340	50
17	205/45R17 XL		88	W	7J	560	1235	340	50
	205/50R17 XL		93	W	61/2J	650	1433	340	50
	215/40R17 XL		87	W	71/2J	545	1201	340	50
	215/45R17 XL		91	W	7J	615	1356	340	50
	215/50R17 XL		95	W	7J	690	1521	340	50
	215/55R17		94	W	7J	670	1477	300	44
	225/45R17 XL		94	W	71/2J	670	1477	340	50
	225/50R17 XL		98	W	7J	750	1653	340	50
	235/45R17 XL		97	W	8J	730	1609	340	50
	245/40R17 XL		95	W	81/2J	690	1521	340	50
	245/45R17 XL		99	W	8J	775	1709	340	50
	18	215/35R18 XL		84	W	71/2J	500	1102	340
215/40R18 XL			89	Y	71/2J	580	1279	340	50
225/40R18 XL			92	Y	8J	630	1389	340	50
225/45R18 XL			95	Y	71/2J	690	1521	340	50
225/50R18			95	W	7J	690	1521	300	44
235/40R18 XL			95	W	81/2J	690	1521	340	50
235/45R18 XL			98	Y	8J	750	1653	340	50
235/50R18			97	Y	71/2J	730	1609	300	44
245/40R18 XL			97	W	81/2J	730	1609	340	50
245/45R18 XL			100	Y	8J	800	1764	340	50
255/45R18 XL			103	W	81/2J	875	1929	340	50
19		225/35R19 XL		88	W	8J	560	1235	340
	235/35R19 XL		91	W	81/2J	615	1356	340	50
	235/40R19 XL		96	Y	81/2J	710	1565	340	50
	245/40R19 XL		98	Y	81/2J	750	1653	340	50
	245/45R19 XL		102	W	8J	850	1874	340	50
	275/30R19 XL		96	W	91/2J	710	1565	340	50
	275/35R19 XL		100	Y	91/2J	800	1764	340	50
	235/45R20 XL		100	W	8J	800	1764	340	50
	245/35R20 XL		95	W	81/2J	690	1521	340	50
	245/40R20 XL		99	Y	81/2J	775	1709	340	50
	245/45R20 XL		103	Y	8J	875	1929	340	50
	245/50R20		102	Y	71/2J	850	1874	300	44
20	255/35R20 XL		97	W	9J	730	1609	340	50
	255/45R20 XL		105	Y	81/2J	925	2039	340	50
	275/30R20 XL		97	Y	91/2J	730	1609	340	50
	275/35R20 XL		102	Y	91/2J	850	1874	340	50
	275/40R20 XL		106	Y	91/2J	950	2094	340	50
	275/45R20 XL		110	V	9J	1060	2337	340	50
	275/55R20 XL		117	W	81/2J	1285	2833	340	50
	225/35R20 XL		90	W	8J	600	1323	340	50
	235/30R22 XL		90	W	81/2J	600	1323	340	50
	245/30R22 XL		92	W	81/2J	630	1389	340	50
	255/30R22 XL		95	W	9J	690	1521	340	50
	265/35R22 XL		102	W	91/2J	850	1874	340	50
22	265/40R22 XL		106	V	91/2J	950	2094	340	50
	285/35R22 XL		106	W	10J	950	2094	340	50
	285/40R22 XL		110	V	10J	1060	2337	340	50
	285/45R22 XL		114	W	91/2J	1180	2601	340	50
	295/25R22 XL		97	W	101/2J	730	1609	340	50
	305/40R22 XL		114	V	11J	1180	2601	340	50
	305/45R22 XL		118	V	10J	1320	2910	340	50
	255/30R24 XL		97	W	9J	730	1609	340	50
	275/25R24 XL		96	W	10J	710	1565	340	50
	295/35R24 XL		110	V	101/2J	1060	2337	340	50
	305/35R24 XL		112	V	11J	1120	2469	340	50
	24	275/25R26 XL		98	W	10J	750	1653	340
295/30R26 XL			107	W	101/2J	975	2149	340	50
305/30R26 XL			109	W	11J	1030	2271	340	50
275/25R28 XL			99	W	10J	775	1709	340	50
28	295/25R28 XL		103	V	101/2J	875	1929	340	50
	275/25R30 XL		101	W	10J	825	1819	340	50

GREEN MAX OPTIMUM HP

PCR High Performance



- > Impressive linear stability & handling performance
- > Outstanding wet and Snow road performance

Mileage Warranty: 60,000Miles
 (Aspect ratio ≥ 60 and speed symbol ≤ T 80,000 miles)



- Multiple variable pitch design to optimize pitch ratio and improve straight-line stability.
- High composite cushion rubber provide excellent handling performance.
- Open shoulder groove and corrugated sipe enhanced the drainage performance.
- New tread compound and lateral sipe density increase the traction on snow road.



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
14	185/60R14		82	H	51/2J	475	1047	300	44
	185/65R14		86	H	51/2J	530	1168	300	44
	195/70R14		91	H	6J	615	1356	300	44
15	185/60R15		84	H	51/2J	500	1102	300	44
	185/65R15		88	H	51/2J	560	1235	300	44
	195/50R15 XL		86	V	6J	530	1168	340	50
	195/55R15		85	V	6J	515	1135	300	44
	195/60R15		88	H	6J	560	1235	300	44
	195/65R15		91	H	6J	615	1356	300	44
	205/60R15		91	H	6J	615	1356	300	44
	205/65R15		94	H	6J	670	1477	300	44
	215/60R15		94	H	61/2J	670	1477	300	44
	215/65R15 XL		100	H	61/2J	800	1764	340	50
16	215/70R15		98	T	61/2J	750	1653	300	44
	225/70R15		100	T	61/2J	800	1764	300	44
	255/70R15		108	S	71/2J	1000	2205	300	44
	205/55R16		91	V	61/2J	615	1356	300	44
	205/60R16		92	H	6J	630	1389	300	44
	205/65R16		95	H	6J	690	1521	300	44
	215/60R16		95	V	61/2J	690	1521	300	44
	215/65R16		98	H	61/2J	750	1653	300	44
	225/55R16		95	V	7J	690	1521	300	44
	225/60R16		98	H	61/2J	750	1653	300	44
17	225/65R16		100	H	61/2J	800	1764	300	44
	225/70R16 XL		107	H	61/2J	975	2149	340	50
	235/60R16		100	H	7J	800	1764	300	44
	235/65R16		103	H	7J	875	1929	300	44
	215/55R17		94	V	7J	670	1477	300	44
	215/60R17		96	H	61/2J	710	1565	300	44
	215/65R17		99	H	61/2J	775	1709	300	44
	225/55R17		97	V	7J	730	1609	300	44
	225/60R17		99	H	61/2J	775	1709	300	44
	225/65R17		102	H	61/2J	850	1874	300	44
18	235/55R17		99	H	71/2J	775	1709	300	44
	235/60R17		102	H	7J	850	1874	300	44
	235/65R17		104	H	7J	900	1984	300	44
	225/55R18		98	H	7J	750	1653	300	44
	235/65R18		106	H	7J	950	2094	300	44

LIGHT TRUCK & SUV TIRE



**OPTIMUM
X/T**



**OPTIMUM
SPORT HP**



**EARTH TRAXX
R/T**



**OPTIMUM
SPORT H/T**



**OPTIMUM
SPORT A/T**



**OPTIMUM
SPORT M/T**





GREEN MAX

OPTIMUM SPORT HP

SUV Ultra High Performance



- > Excellent handling and steering performance
- > Good braking performance
- > Excellent snow performance

Mileage Warranty: 60,000 Miles



- Asymmetric pattern design provides a perfect balance for both dry and wet grip, with inside areas excelling in wet braking while outside shoulders provide superior steering precision and handling.
- Continuous shoulder rib design improves the shoulder stiffness and high speed stability.
- Four wide longitudinal grooves and shoulder lateral grooves provide impressive hydroplaning resistance capability and greater wet traction.
- Deep herringbone sipes on shoulder blocks drain water away to improve wet & snow performance.




RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		
						kg	lbs	kPa	psi	
15	205/70R15		96	H	6J	710	1565	300	44	
	235/70R15 XL		106	H	7J	950	2094	340	50	
	205/70R16		97	V	6J	730	1609	300	44	
	215/65R16 XL		102	H	61/2J	850	1874	340	50	
	215/70R16		100	H	61/2J	800	1764	300	44	
	225/60R16		98	H	61/2J	750	1653	300	44	
16	225/75R16		104	H	6J	900	1984	300	44	
	235/70R16		106	H	7J	950	2094	300	44	
	245/70R16 XL		111	H	7J	1090	2403	340	50	
	265/70R16		112	H	8J	1120	2469	300	44	
	275/70R16		114	H	8J	1180	2601	300	44	
	215/60R17		96	H	61/2J	710	1565	300	44	
17	225/55R17 XL		101	V	7J	825	1819	340	50	
	225/60R17		99	H	61/2J	775	1709	300	44	
	225/65R17		102	H	61/2J	850	1874	300	44	
	235/55R17 XL		103	W	71/2J	875	1929	340	50	
	235/60R17 XL		106	V	7J	950	2094	340	50	
	235/65R17 XL		108	V	7J	1000	2205	340	50	
	235/70R17 XL		109	T	7J	1030	2271	340	50	
	245/65R17 XL		111	H	7J	1090	2403	340	50	
	255/60R17		106	H	71/2J	950	2094	300	44	
	255/65R17		110	H	71/2J	1060	2337	300	44	
	255/70R17		112	T	71/2J	1120	2469	300	44	
	265/65R17		112	H	8J	1120	2469	300	44	
18	275/55R17		109	V	81/2J	1030	2271	300	44	
	225/60R18		100	H	61/2J	800	1764	300	44	
	235/55R18 XL		104	V	71/2J	900	1984	340	50	
	235/60R18 XL		107	W	7J	975	2149	340	50	
	235/65R18		106	H	7J	950	2094	300	44	
	245/60R18		105	V	7J	925	2039	300	44	
	255/55R18 XL		109	V	8J	1030	2271	340	50	
	255/60R18 XL		112	V	71/2J	1120	2469	340	50	
	255/65R18		111	H	71/2J	1090	2403	300	44	
	255/70R18		113	T	71/2J	1150	2535	300	44	
	265/60R18		110	H	8J	1060	2337	300	44	
	265/65R18		114	H	8J	1180	2601	300	44	
19	265/70R18		116	T	8J	1250	2756	300	44	
	275/60R18		113	H	8J	1150	2535	300	44	
	275/65R18		116	H	8J	1250	2756	300	44	
	235/55R19 XL		105	V	71/2J	925	2039	340	50	
	245/55R19		103	V	71/2J	875	1929	300	44	
	255/50R19 XL		107	W	8J	975	2149	340	50	
	255/60R19		109	H	71/2J	1030	2271	300	44	
	255/55R19 XL		111	V	8J	1090	2403	340	50	
	20	255/50R20 XL		109	V	8J	1030	2271	340	50
		275/60R20		115	T	8J	1215	2679	300	44

GREEN MAX

OPTIMUM SPORT H/T

Highway-Terrain



- > Delivers superb handling in changing weather conditions
- > Outstanding dry&wet braking performance

Mileage Warranty: 65,000Miles



- Stiff shoulder blocks enhance cornering grip for better steering response and stability.
- Multi-angled siping design optimizes void-to-fill ratio, provides exceptional handling throughout all seasons.
- Four circumferential grooves increase the drainage capacity and grip on wet roads.




RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15	235/75R15 XL		109	T	61/2J	1030	2271	340	50
	31×10.50R15LT	6PR	109	R	81/2J	1030	2270	350	50
16	225/70R16		103	T	61/2J	875	1929	300	44
	245/75R16		111	T	7J	1090	2403	300	44
	255/70R16		111	T	71/2J	1090	2403	300	44
	265/75R16		116	T	71/2J	1250	2756	300	44
	LT215/85R16	10PR	115/112	S	6J	D1120 S1215	D2470 S2680	550	80
	LT225/75R16	10PR	115/112	S	6J	D1120 S1215	D2470 S2680	550	80
	LT235/85R16	10PR	120/116	R	61/2J	D1260 S1380	D2778 S3042	550	80
	LT245/75R16	10PR	120/116	R	7J	D1260 S1380	D2778 S3042	550	80
LT265/75R16	10PR	123/120	R	71/2J	D1400 S1550	D3085 S3415	550	80	
17	235/65R17		104	T	7J	900	1984	300	44
	245/70R17		110	T	7J	1060	2337	300	44
	265/65R17		112	T	8J	1120	2469	300	44
	265/70R17		115	T	8J	1215	2679	300	44
	275/65R17		115	S	8J	1215	2679	300	44
	285/65R17		116	S	81/2J	1250	2756	300	44
	LT235/80R17	10PR	120/117	R	61/2J	D1285 S1400	D2835 S3085	550	80
	LT245/75R17	10PR	121/118	R	7J	D1320 S1450	D2910 S3195	550	80
	LT265/70R17	10PR	121/118	R	8J	D1320 S1450	D2910 S3195	550	80
	LT285/70R17	10PR	121/118	S	81/2J	D1320 S1450	D2910 S3195	550	80
18	LT265/70R18	10PR	124/121	R	8J	D1450 S1600	D3195 S3525	550	80
	LT275/65R18	10PR	123/120	S	8J	D1285 S1550	D2835 S3415	550	80
	LT275/70R18	10PR	125/122	S	8J	D1400 S1650	D3085 S3640	550	80
20	265/50R20 XL		111	H	81/2J	1090	2403	340	50
	275/55R20 XL		117	T	81/2J	1285	2833	340	50

GREEN MAX

OPTIMUM SPORT A/T

All-Terrain



- > Perfect grip on snowy surfaces
- > Outstanding off-road traction

Mileage Warranty: 55,000 Miles



- Upper sidewall featured with buttress design increases aesthetic elements, meanwhile delivers substantial grip and forward momentum even at low pressure.
- Staggered sidewall lugs combined with tie-bars in-between increase shoulder stiffness and bring excellent off road traction.
- Increased density of lateral sipe provide outstanding traction on snow road.



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15	235/75R15 XL OWL		109	T	61/2J	1030	2271	340	50
	265/70R15 OWL		112	T	8J	1120	2469	300	44
	LT235/75R15	6PR	104/101	R	61/2J	D825 S900	D1820 S1985	350	50
	30X9.50R15LT OWL	6PR	104	S	71/2J	900	1985	350	50
	31X10.50R15LT OWL	6PR	109	R	81/2J	1030	2270	350	50
16	235/70R16 OWL		106	T	7J	950	2094	300	44
	245/70R16 XL OWL		111	T	7J	1090	2403	340	50
	245/75R16 OWL		111	T	7J	1090	2403	300	44
	255/70R16		111	S	71/2J	1090	2403	300	44
	265/70R16 OWL		112	T	8J	1120	2469	300	44
	265/75R16 OWL		116	T	71/2J	1250	2756	300	44
	LT215/85R16	10PR	115/112	Q	6J	D1120 S1215	D2470 S2680	550	80
	LT225/75R16 OWL	10PR	115/112	Q	6J	D1120 S1215	D2470 S2680	550	80
	LT235/85R16 OWL	10PR	120/116	S	61/2J	D1260 S1380	D2778 S3042	550	80
	LT245/75R16 OWL	10PR	120/116	Q	7J	D1260 S1380	D2778 S3042	550	80
17	LT265/75R16 OWL	10PR	123/120	R	71/2J	D1400 S1550	D3085 S3415	550	80
	LT285/75R16	10PR	126/123	R	8J	D1550 S1700	D3415 S3750	550	80
	LT305/70R16 OWL	10PR	124/121	R	9J	D1450 S1600	D3195 S3525	450	65
	245/65R17 XL OWL		111	T	7J	1090	2403	340	50
	245/70R17 OWL		110	S	7J	1060	2337	300	44
	265/65R17		112	T	8J	1120	2469	300	44
	265/70R17		115	T	8J	1215	2679	300	44
	285/70R17 OWL		116	T	81/2J	1250	2756	300	44
	LT235/80R17 OWL	10PR	120/117	R	61/2J	D1285 S1400	D2835 S3085	550	80
	LT245/75R17 OWL	10PR	121/118	R	7J	D1320 S1450	D2910 S3195	550	80
18	LT265/70R17 OWL	10PR	121/118	R	8J	D1320 S1450	D2910 S3195	550	80
	LT285/70R17 OWL	8PR	121/118	S	81/2J	D1320 S1450	D2910 S3195	450	65
	LT285/70R17 OWL	10PR	121/118	S	81/2J	D1320 S1450	D2910 S3195	450	65
	LT305/70R17 OWL	8PR	119/116	R	9J	D1250 S1360	D2755 S3000	350	50
	255/70R18 OWL		113	S	71/2J	1150	2535	300	44
	265/70R18 OWL		116	T	8J	1250	2756	300	44
	275/65R18		116	T	8J	1250	2756	300	44
	LT265/65R18 OWL	10PR	122/119	Q	8J	D1360 S1500	D3000 S3305	550	80
	LT265/70R18 OWL	10PR	124/121	S	8J	D1450 S1600	D3195 S3525	550	80
	LT275/65R18 OWL	10PR	123/120	S	8J	D1400 S1550	D3085 S3415	550	80
20	LT275/70R18 OWL	10PR	125/122	S	8J	D1500 S1650	D3305 S3640	550	80
	LT305/60R18 OWL	10PR	121/118	R	9J	D1320 S1450	D2910 S3195	450	65
	275/55R20 OWL		113	S	81/2J	1150	2535	300	44
	275/60R20 OWL		115	T	8J	1215	2679	300	44
	LT275/55R20 OWL	10PR	120/117	Q	81/2J	D1285 S1400	D2835 S3085	550	80
	LT275/60R20	10PR	123/120	Q	8J	D1400 S1550	D3085 S3415	550	80
	LT275/65R20 OWL	10PR	126/123	S	8J	D1550 S1700	D3415 S3750	550	80
	LT285/55R20	10PR	122/119	S	9J	D1360 S1500	D3000 S3305	550	80
	LT305/55R20 OWL	10PR	121/118	R	91/2J	D1320 S1450	D2910 S3195	450	65
	35X12.50R20LT OWL	10PR	121	Q	10J	1450	3195	450	65

GREEN MAX OPTIMUM X/T

Extreme All-Terrain



- > Outstanding off-road traction
- > Outstanding dry&wet breaking performance

Mileage Warranty: 55,000Miles



- 1 Large tread blocks, wide tread arc width design and optimized pitch design provide extraordinary
- 2 With the patented e-I Max, the design of the high-strength three-ply carcass can handle all kinds of con
- 3 High-density sipes offer excellent handling and snow/wet traction
- 4 Wide grooves improve hydroplaning resistance, wet braking and mud traction



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16	265/70R16 XL		116	T	8J	1250	2756	340	50
	265/75R16		116	T	7 1/2J	1250	2756	300	44
	LT265/75R16	10PR	123/120	Q	7 1/2J	D1400 S1550	D3085 S3415	550	80
	LT285/75R16	10PR	126/123	Q	8J	D1550 S1700	D3415 S3750	550	80
	LT295/75R16	10PR	128/125	Q	8J	D1650 S1800	D3640 S3970	550	80
	LT305/70R16	10PR	124/121	Q	9J	D1450 S1600	D3195 S3525	450	65
	LT315/75R16	10PR	127/124	Q	8 1/2J	D1600 S1750	D3525 S3860	450	65
17	265/65R17 XL		116	T	8J	1250	2756	340	50
	265/70R17		115	T	8J	1215	2679	300	44
	285/70R17		116	Q	8 1/2J	1250	2756	300	44
	33X12.50R17LT	10PR	120	R	10J	1400	3085	450	65
	35X12.50R17LT	10PR	125	R	10J	1650	3640	450	65
	37X12.50R17LT	8PR	124	Q	10J	1600	3525	350	50
	37X13.50R17LT	10PR	121	Q	11J	1450	3195	450	65
	LT255/80R17	10PR	121/118	Q	7J	D1320 S1450	D2910 S3195	550	80
	LT265/70R17	10PR	123/120	Q	8J	D1400 S1550	D3085 S3415	550	80
	LT285/70R17	10PR	121/118	Q	8 1/2J	D1320 S1450	D2910 S3195	550	80
	LT285/75R17	10PR	121/118	Q	8J	D1320 S1450	D2910 S3195	550	80
	LT295/70R17	10PR	121/118	Q	8 1/2J	D1320 S1450	D2910 S3195	550	80
	LT305/70R17	10PR	121/118	Q	9J	D1320 S1450	D2910 S3195	450	65
LT315/70R17	10PR	126/123	Q	9 1/2J	D1550 S1700	D3415 S3750	450	65	
18	255/55R18 XL		109	T	8J	1030	2271	340	50
	255/70R18 XL		116	T	7 1/2J	1250	2756	340	50
	265/60R18 XL		114	S	8J	1180	2601	340	50
	265/65R18 XL		116	T	8J	1250	2756	340	50
	265/70R18		116	S	8J	1250	2756	300	44
	275/65R18 XL		116	T	8J	1250	2756	300	44
	285/60R18 XL		120	T	8 1/2J	1400	3086	340	50
305/60R18		116	Q	9J	1250	2756	300	44	

OPTIMUM X/T

OPTIMUM X/T

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
18	33X12.50R18LT	12PR	122	R	10J	1500	3305	550	80
	35X12.50R18LT	10PR	123	R	10J	1550	3415	450	65
	37X11.50R18LT	8PR	127	Q	9J	1750	3860	450	65
	37X12.50R18LT	10PR	128	Q	10J	1800	3970	550	80
	37X13.50R18LT	8PR	124	Q	11J	1600	3525	350	50
	LT265/65R18	10PR	122/119	Q	8J	D1360 S1500	D3000 S3305	550	80
	LT265/70R18	10PR	124/121	Q	8J	D1450 S1600	D3195 S3525	550	80
	LT275/65R18	10PR	123/120	Q	8J	D1400 S1550	D3085 S3415	550	80
	LT275/70R18	10PR	125/122	Q	8J	D1500 S1650	D3305 S3640	550	80
	LT285/60R18	10PR	122/119	Q	8 1/2J	D1360 S1500	D3000 S3305	550	80
	LT285/65R18	10PR	125/122	Q	8 1/2J	D1500 S1650	D3305 S3640	550	80
	LT285/70R18	10PR	127/124	Q	8 1/2J	D1600 S1750	D3525 S3860	550	80
	LT285/75R18	10PR	129/126	Q	8J	D1700 S1850	D3750 S4080	550	80
	LT295/70R18	10PR	129/126	Q	8 1/2J	D1700 S1850	D3750 S4080	550	80
	LT305/65R18	12PR	128/125	Q	9J	D1650 S1800	D3640 S3970	550	80
	LT325/60R18	10PR	124/121	Q	9 1/2J	D1450 S1600	D3195 S3525	450	65
LT325/65R18	10PR	127/124	Q	9 1/2J	D1600 S1750	D3525 S3860	450	65	
20	265/50R20 XL		111	T	8 1/2J	1090	2403	340	50
	275/55R20 XL		117	T	8 1/2J	1285	2833	340	50
	285/50R20 XL		116	Q	9J	1250	2756	300	44
	305/50R20 XL		120	Q	9 1/2J	1400	3086	340	50
	305/55R20		116	Q	9 1/2J	1250	2756	300	44
	33X12.50R20LT	12PR	119	R	10J	1360	3000	550	80
	35X11.50R20LT	10PR	124	Q	9J	1600	3525	550	80
	35X12.50R20LT	12PR	125	Q	10J	1650	3640	550	80
	35X13.50R20LT	12PR	126	Q	11J	1700	3750	550	80
	37X12.50R20LT	10PR	126	Q	10J	1700	3750	450	65
37X13.50R20LT	10PR	127	Q	11J	1750	3860	450	65	

RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure		
						kg	lbs	kPa	psi	
20	38X13.50R20LT	10PR	128	Q	11J	1800	3970	450	65	
	LT265/60R20	10PR	121/118	Q	8J	D1320 S1450	D2910 S3195	550	80	
	LT275/55R20	10PR	120/117	S	8 1/2J	D1285 S1400	D2835 S3085	550	80	
	LT275/60R20	10PR	123/120	Q	8J	D1400 S1550	D3085 S3415	550	80	
	LT275/65R20	10PR	126/123	Q	8J	D1550 S1700	D3415 S3750	550	80	
	LT285/55R20	10PR	122/119	S	9J	D1360 S1500	D3000 S3305	550	80	
	LT285/60R20	10PR	125/122	Q	8 1/2J	D1500 S1650	D3305 S3640	550	80	
	LT285/65R20	10PR	127/124	Q	8 1/2J	D1600 S1750	D3525 S3860	550	80	
	LT295/55R20	10PR	123/120	Q	9 1/2J	D1400 S1550	D3085 S3415	550	80	
	LT295/60R20	10PR	126/123	Q	8 1/2J	D1550 S1700	D3415 S3750	550	80	
	LT295/65R20	10PR	129/126	Q	8 1/2J	D1700 S1850	D3750 S4080	550	80	
	LT305/55R20	12PR	125/122	Q	9 1/2J	D1500 S1650	D3305 S3640	550	80	
	LT325/60R20	10PR	126/123	Q	9 1/2J	D1550 S1700	D3415 S3750	450	65	
	22	33X12.50R22LT	12PR	114	R	10J	1180	2600	550	80
		35X12.50R22LT	12PR	121	R	10J	1450	3195	550	80
		37X12.50R22LT	12PR	127	Q	10J	1750	3860	550	80
37X13.50R22LT		12PR	128	Q	11J	1800	3970	550	80	
38X13.50R22LT		10PR	126	Q	11J	1700	3750	450	65	
38X15.50R22LT		10PR	128	Q	12 1/2J	1800	3970	450	65	
LT285/50R22		10PR	121/118	Q	9J	D1320 S1450	D2910 S3195	550	80	
LT285/55R22		10PR	124/121	Q	9J	D1450 S1600	D3195 S3525	550	80	
LT325/50R22		12PR	127	Q	10J	1750	3860	550	80	
24		37X13.50R24LT	12PR	124	Q	11J	1600	3525	550	80
	38X13.50R24LT	12PR	127	Q	11J	1750	3860	550	80	
	38X15.50R24LT	12PR	128	Q	12 1/2J	1800	3970	550	80	
	LT315/50R24	12PR	127/124	Q	10J	D1600 S1750	D3525 S3860	550	80	

GREEN MAX

EARTH TRAXX R/T

Rugged-Terrain



- > Outstanding off-road traction
- > Durable construction

Mileage Warranty: 50,000 Miles


- 1 Staggered angular blocks and ledges between lugs capable of removing sticky clods enhance off-road grip on muddy and sandy surfaces
- 2 Wide lateral zigzag grooves ensure superb off-road traction in the whole lifetime
- 3 High-strength three-ply carcass design along with sidewall adopting E-L Max patented technology provides impact and puncture resistance
- 4 High strength cord protect sidewall from puncture of rugged rock, also can enhancing driving and riding safety

RIM	Size	Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
16	LT265/75R16	10PR	123/120	Q	7 1/2J	S1550 D1400	S3415 D3085	550	80
	LT285/75R16	10PR	126/123	Q	8J	S1700 D1550	S3750 D3415	550	80
17	265/70R17	/	115	T	8J	1215	2679	300	44
	33X12.50R17LT	10PR	120	Q	10J	1400	3085	450	65
	35X12.50R17LT	12PR	128	Q	10J	1800	3970	550	80
	37X12.50R17LT	12PR	128	Q	10J	1800	3970	550	80
	LT265/70R17	10PR	123/120	Q	8J	S1550 D1400	S3415 D3085	550	80
	LT285/70R17	10PR	126/123	Q	8 1/2J	S1700 D1550	S3750 D3415	550	80
18	275/65R18	/	116	T	8J	1250	2756	300	44
	33X12.50R18LT	12PR	122	Q	10J	1500	3305	550	80
	35X12.50R18LT	12PR	128	Q	10J	1800	3970	550	80
	37X12.50R18LT	12PR	128	Q	10J	1800	3970	550	80
	LT275/65R18	10PR	123/120	Q	8J	S1550 D1400	S3415 D3085	550	80
	LT275/70R18	10PR	125/122	Q	8J	S1650 D1500	S3640 D3305	550	80
20	275/55R20	XL	117	T	8 1/2J	1285	2833	340	50
	275/60R20	XL	116	T	8J	1250	2756	340	50
	33X12.50R20LT	12PR	119	Q	10J	1360	3000	550	80
	35X12.50R20LT	12PR	125	Q	10J	1650	3640	550	80
	35X13.50R20LT	12PR	126	Q	11J	1700	3750	550	80
	37X12.50R20LT	12PR	128	Q	10J	1800	3970	550	80
	LT275/55R20	10PR	120/117	Q	8 1/2J	S1400 D1285	S3085 D2835	550	80
	LT275/65R20	10PR	126/123	Q	8J	S1700 D1550	S3750 D3415	550	80
	LT285/55R20	10PR	122/119	S	9J	S1500 D1360	S3305 D3000	550	80
	LT285/60R20	10PR	125/122	Q	8 1/2J	S1650 D1500	S3640 D3305	550	80
22	LT305/55R20	12PR	125/122	Q	9 1/2J	S1650 D1500	S3640 D3305	550	80
	33X12.50R22LT	12PR	114	Q	10 1/2J	1180	2600	550	80
	35X12.50R22LT	12PR	121	Q	10J	1450	3195	550	80
	37X12.50R22LT	12PR	127	Q	10J	1750	3860	550	80
	37X13.50R22LT	12PR	128	Q	11J	1800	3970	550	80

GREEN MAX

OPTIMUM SPORT M/T

Mud-Terrain



- > Outstanding traction on mud terrain
- > Excellent off-road durability



- The unique dual layer tread design provides excellent off-road traction and grip.
- Tread blocks with reinforced foundation underneath and chamfered edge prevent irregular wear to prolong tire's service life.
- The aggressive sidewall lugs maintain strong resistance to cutting/chipping in rugged terrain, dedicated to stone ejection and improved driving safety.



RIM	Size	Ply Rating	Load index	Speed Symbols	Standard Rim	Standard Load		Max Pressure	
						kg	lbs	kPa	psi
15	LT215/75R15	6PR	100/97	Q	6J	D730 S800	D1610 S1765	350	50
	LT235/75R15	6PR	104/101	Q	61/2J	D825 S900	D1820 S1985	350	50
	30x9.50R15LT	6PR	104	Q	71/2J	900	1985	350	50
	31x10.50R15LT	6PR	109	Q	81/2J	1030	2270	350	50
	33x12.50R15LT	6PR	108	Q	10J	1000	2205	250	36
16	LT225/75R16	8PR	110/107	Q	6J	D975 S1060	D2150 S2335	450	65
	LT235/85R16	10PR	120/116	Q	61/2J	D1250 S1400	D2755 S3085	550	80
	LT245/75R16	10PR	120/116	Q	7J	D1260 S1380	D2778 S3042	550	80
	LT265/70R16	6PR	110/107	Q	8J	D975 S1060	D2150 S2335	350	50
	LT265/75R16	10PR	123/120	Q	71/2J	D1550 S1400	D3085 S3415	550	80
	LT285/75R16	10PR	126/123	Q	8J	D1550 S1700	D3415 S3750	550	80
	LT305/70R16	10PR	124/121	Q	9J	D1450 S1600	D3195 S3525	450	65
	LT315/75R16	10PR	127/124	Q	81/2J	D1600 S1750	D3525 S3860	450	65
17	LT235/80R17	10PR	120/117	Q	61/2J	D1285 S1400	D2835 S3085	550	80
	LT265/70R17	10PR	121/118	Q	8J	D1320 S1450	D2910 S3195	550	80
	LT285/70R17	10PR	121/118	Q	81/2J	D1320 S1450	D2910 S3195	450	65
	LT305/70R17	8PR	119/116	Q	9J	D1250 S1360	D2755 S3000	350	50
	33x12.50R17LT	10PR	120	Q	10J	1400	3085	450	65
	37x13.50R17LT	10PR	121	Q	11J	1450	3195	450	65
18	35x12.50R17LT	10PR	121	Q	10J	1450	3195	450	65
	LT275/70R18	10PR	125/122	Q	8J	D1500 S1650	D3305 S3640	550	80
	33x12.50R18LT	10PR	118	Q	10J	1320	2910	450	65
	33x12.50R18LT	12PR	122	Q	10J	1500	3305	550	80
	35x12.50R18LT	10PR	123	Q	10J	1550	3415	450	65
20	35x12.50R18LT	12PR	128	Q	10J	1800	3970	550	80
	LT275/55R20	10PR	120/117	Q	81/2J	D1285 S1400	D2835 S3085	550	80
	LT285/55R20	10PR	122/119	Q	9J	D1360 S1500	D3000 S3305	550	80
	LT285/65R20	10PR	127/124	Q	81/2J	D1600 S1750	D3525 S3860	550	80
	LT305/55R20	10PR	121/118	Q	91/2J	D1320 S1450	D2910 S3195	450	65
	33x12.50R20LT	10PR	114	Q	10J	1180	2600	450	65
	33x12.50R20LT	12PR	119	Q	10J	1360	3000	550	80
	35x12.50R20LT	10PR	121	Q	10J	1450	3195	450	65
22	35x12.50R20LT	12PR	125	Q	10J	1650	3640	550	80
	37x13.50R20LT	10PR	127	Q	11J	1750	3860	450	65
	37x13.50R20LT	12PR	128	Q	11J	1800	3970	550	80
	33x12.50R22LT	10PR	109	Q	10J	1030	2270	450	65
	33x12.50R22LT	12PR	114	Q	10J	1180	2600	550	80
	35x12.50R22LT	10PR	117	Q	10J	1285	2835	450	65
	35x12.50R22LT	12PR	121	Q	10J	1450	3195	550	80
24	37x13.50R22LT	10PR	123	Q	11J	1550	3415	450	65
	37x13.50R22LT	12PR	128	Q	11J	1800	3970	550	80
	37x13.50R24LT	10PR	120	Q	11J	1400	3085	450	65
26	37x13.50R26LT	10PR	114	Q	11J	1180	2600	450	65

Warranty Eligibility

This limited warranty applies to all the qualified replacement market Passenger and Light Truck Tires produced by Shandong Linglong Tyre Co., Ltd. and all its subsidiaries. This Limited Warranty only applies to the original purchaser, and the tire has a complete brand identification, DOT or barcode, and it is valid if all of the following apply:

- The tires are manufactured after January 1, 2025, and are shipped to North America for sale and use.
- The tire fails due to the workmanship or materials.
- The tire shall not exceed the warranty period, and the remaining pattern shall not be less than TWI.

What is warranted and for how long

If the tire covered by this limited warranty become unusable due to a workmanship or material related condition during its usable tread depth is more than TWI, LingLong will provide compensation on the following conditions:

- The warranty period is 6 years from the date of purchase, or 7 years from the date of production, whichever comes first, and the remaining pattern depth is not less than TWI.
- If the tire fails due to manufacturing reasons and meets the warranty scope and conditions, the remaining pattern depth exceeds TWI, the new tire of the same specification will be covered free of charge.

What is not covered

1. Road hazard injuries or damages caused by obstacles or debris, such as cuts, punctures (whether repairable or not), snags, bruises, tears, abrasions or impact breaks.
2. Improper repairs or repairs that have failed.
3. Improper inflation or other maintenance abuses.
4. Improper mounting/dismounting.
5. Mechanical irregularities such as bent wheel assemblies, misalignment worn or faulty components.
6. Accident, corrosion, tire alteration, vandalism, fire, theft or damages cause by nature.
7. Damage from over-inflation or under-inflation, overloading, defective vehicle mechanical conditions.
8. Non-racing or off-road tires that are misused or abused for racing or off-road purposes.
9. Ozone or weather cracking or other abuse, misuse, tire alteration, run flat.
10. Tire which D.O.T identification number and/or brand name removed intentionally.
11. Tires that have been modified after leaving the factory, such as fillers, sealants, balancing substances and external tire treatments or materials of any kind. If the added material is the cause of a failure, a tire will not be accepted for warranty claim.
12. Abnormal tread wear resulting from improper installation, wheel misalignment, tire/wheel assembly imbalance, etc.
13. Vehicles or tires operated in excess of the rated Work Capacity Factor.
14. Additional monetary loss, such as damage of the vehicle or time, etc.

Road Hazard Warranty

If a tire is rendered unserviceable due to a non-repairable road hazard, it must meet following guidelines:

- Tire must be within one year from date of purchase. The tire purchase certificate must be provided.
- For qualifying tires, 50% of the claim will be given based on the total of the tire FOB price and freight. Calculation method: Compensation = (FOB+Freight)*50%

Treadwear Mileage Warranty

If an eligible tire evenly wears out before the warranty miles under the normal passenger use, and within the Limited Warranty time period, if the tire pattern is worn to TWI and does not reach the warranty mileage, the unused service will be subsidized on a pro-rata basis to purchase a new tire. To make a claim, installation record, tire rotation record, and the removal record must all be forwarded with the claimed tire.

- Tires must be rotated every 6,000 to 8,000 miles or less.
- This warranty is not applicable to original equipment tires.
- Treadwear Mileage Warranty only applies to the original purchaser/owner of the tires.
- Mileage Warranty does not apply to tires used in commercial applications, including, but not limited to: law enforcement, taxi services, courier services ect.
- Tires must be evenly worn, with a depth difference of less than 2/32nds across the tread.
- Mileage warranty product list:

NO.	Brand	Pattern	Mileage Warranty(miles)
1	GREENMAX	OPTIMUM HP	60,000
2	GREENMAX	OPTIMUM UHP	50,000
3	GREENMAX	OPTIMUM SPORT HP	60,000
4	GREENMAX	OPTIMUM SPORT H/T	65,000
5	GREENMAX	OPTIMUM SPORT A/T	65,000
6	GREENMAX	OPTIMUM X/T	55,000
7	GREENMAX	EARTH TRAXX R/T	50,000

90-DAY Customer Satisfaction Trial

LingLong offers a 90 Day Free Trial as the following :

- Applies Passenger Tires (Excluding tires for commercial and racing purposes, etc.), Light Truck tires not included.
- This satisfaction guarantee applies to the original purchaser who purchases at least four new passenger tires at one-time and not to the tires provided under this guarantee.
- Not applicable to tires that are intentionally damaged or damaged due to improper use.
- How do you return your tires during the trial period?
- Within the authorized time frame from the date of purchase, you must return your tires to the tire dealer where you purchased your tires.
- Present the original sales receipt and proof-of-purchase.
- Truthfully state reason for dissatisfaction (such as appearance, driving, etc.).

To make a claim under this limited warranty

1. Present your tires and the original purchase receipt to point of purchase or any the Company' s dealer.
2. Complete and sign the Claim Adjustment form provided, keep a copy for your records and leave the tire with the dealer to process the warranty claim.

Owner' s obligation

1. At the time of purchase, tires must be properly installed with recommended inflation and balanced. Observe rotation and alignment regularly according to recommendations.
2. Refer to any authorized the Company' s dealer or point of purchase for adjustment claim.
3. Owner is responsible for service charges and applicable taxes.
4. Submit a copy of the original purchase receipt to support the adjustment claim.

Tire safety and maintenance

Tire failure can result in serious damage and/or personal injury. To reduce these risks we recommend the following:

1. Maintain proper inflation, do not under or over inflate. Always maintain inflation according to the vehicle manufacturer' s or the Company' s recommendations.
2. Wheel alignment and balancing should be checked at regular intervals.
3. Do not overload, refer to load carrying capacity information molded on tire sidewall.
4. Avoid spinning, driving over curbs, potholes, obstacles and edges of pavement.
5. Never drive with smooth(bald) tires. By law, tires must be replaced when worn to TWI (tread wear indicator).
6. Check your tires frequently for any damage such as scrapes, cuts, foreign objects, separations or bulges. If damaged replace it with spare and refer to an authorized dealer.
7. Do not drive in excess of permitted speed limits and beyond the maximum specified by tire.
8. To achieve proper wear and optimize tread life, rotate your tires at least every 6000 miles.

Exclusions, Limitations, and Legal Rights

No representative or dealer is authorized to make any representation, promise, or agreement on behalf of Linglong, except as expressly stated in this document. Any tire, regardless of construction quality, may fail in service or otherwise become unserviceable due to conditions beyond the manufacturer's control. This warranty does not constitute a representation that tire failure will not occur under any circumstances.

DISCLAIMER: This warranty is provided in lieu of all other warranties and representations, express or implied. Linglong expressly disclaims any and all implied warranties, including but not limited to the implied warranties of merchantability and fitness for a particular purpose. No other warranty or representation of any kind shall be deemed to exist or arise by operation of law.

LIMITATION OF DAMAGES: Under no circumstances shall Linglong be liable for any indirect, special, incidental, consequential, or punitive damages, including but not limited to loss of profits, business interruption, loss of reputation or goodwill, or costs related to replacement transportation or other associated expenses. Certain states or provinces do not allow the exclusion or limitation of incidental or consequential damages; therefore, some portions of this limitation may not be enforceable in specific jurisdictions.

This warranty sets forth specific legal obligations, and additional rights may apply depending on the governing state or provincial law.