

MIRAGE

CATÁLOGO DE LLANTAS 2024



Blvd. Campestre No. 72
Col. Casa Blanca, León, Gto.
C.P. 37170



+52 (477) 718.09.21
01800 000TIRE (8473)



info@tiredirect.com.mx
www.tiredirect.com.mx




Tire Direct



Tire Direct

QUALIFICATIONS



DIRECTORY

ALL POSITION




12R22.5-18

MG117 P1




12.00R24-20
315/80R22.5-20

MG122 P1




10.00R20-18
11.00R20-18
12.00R20-18

MG307 P2




6.50R16-12
7.00R16-14
7.50R16-14
8.25R16-16
8.25R20-16
9.00R20-16
10.00R20-18
11.00R20-18
12.00R24-20
11R22.5-16
12R22.5-18
13R22.5-20

MG702 P2




9.00R20-16
10.00R20-18
11.00R20-18
12.00R20-18

MG708 P3




315/80R22.5-20

ST011 P3



11R22.5-14
11R22.5-16
12R22.5-18
295/80R22.5-18

FAR515 P4



11R22.5-16
12R22.5-18
295/80R22.5-18
315/80R22.5-20
12.00R24-20


FAM517 P4

STEER AND TRAILER




MG111 P5

11R22.5-16
11R24.5-14
11R24.5-16
215/75R17.5-16
225/70R19.5-14
235/75R17.5-16
245/70R19.5-16
255/70R22.5-16
285/75R24.5-14
285/75R24.5-16
295/75R22.5-14
295/75R22.5-16



MG121 P5

8.25R16-16
9.5R17.5-16
295/80R22.5-18
315/70R22.5-20
315/80R22.5-20



MG607 P8

12.00R24-20




MG660 P8

11R22.5-16
12R22.5-18
13R22.5-20
215/75R17.5-16
255/70R22.5-16
295/80R22.5-18
315/70R22.5-20
315/80R22.5-20



MG123 P6

11.00R20-18



MG124 P6

315/80R22.5-20



MG668 P9

295/80R22.5-18



FAR518 P9

225/75R17.5-14
245/70R17.5-16
245/70R17.5-18
245/70R19.5-16
245/70R19.5-18
265/70R19.5-16
265/70R19.5-18
285/70R19.5-16
285/70R19.5-18



MG330 P7

11R22.5-16
12R22.5-18



MG606/606+ P7

9.00R20-16
10.00R20-18
11.00R20-18
12.00R20-18
11R22.5-16
315/80R22.5-20

DRIVE



MG303 P10

7.00R16-14
7.50R16-14
8.25R16-16
8.25R20-16
9.00R20-16
10.00R20-18
11.00R20-18
12.00R20-18



MG312 P10

11R22.5-16
11R24.5-14
11R24.5-16
285/75R24.5-14
285/75R24.5-16
295/75R22.5-14
295/75R22.5-16




MG638/MG638+ P13

10.00R20-18
11R22.5-16
12R22.5-18
315/70R22.5-20
315/80R22.5-20



MG900/MG668 P13

10.00R20-18
295/80R22.5-18



MG313 P11

7.50R16-14
8.25R16-16
8.25R20-16
9.00R20-16
10.00R20-18
11.00R20-18
12.00R20-18



MG322 P11

12.00R24-20
315/80R22.5-20



MG701 P14

10.00R20-18
11.00R20-18
12.00R20-18
12R22.5-18



MG706 P14

7.00R16-14
7.50R16-14
8.25R16-16
8.25R20-16
9.00R20-16
10.00R20-18
11.00R20-18
12.00R20-18



MG505 P12

10.00R20-18



MG628 P12

11R22.5-16
12R22.5-18
13R22.5-20
215/75R17.5-16
235/75R17.5-16
315/70R22.5-20
295/80R22.5-18
315/80R22.5-20



MG729 P15

10.00R20-18
11.00R20-18
12.00R20-18
12.00R24-20



MG768 P15

10.00R20-18
11.00R20-18
12.00R20-18
12R22.5-18
13R22.5-20
315/80R22.5-20

TRAILER



FTL311 P16

385/55R22.5-20
385/65R22.5-20
425/65R22.5-20
445/65R22.5-20



FTM313 P16

385/65R22.5-20



MG618 P17


11R22.5-16
12R22.5-18
295/75R22.5-14
295/75R22.5-16



ST022 P17

235/75R17.5-16
385/65R22.5-20

OFF THE ROAD




MG168 P18

7.00R16-14
7.50R16-14
8.25R16-16
8.25R20-16
9.00R20-16
10.00R20-18




MG318 P18

8.25R20-16
10.00R20-18
11.00R20-18
12.00R20-18
295/80R22.5-18



MG320 P19

295/80R22.5-18



MG321 P19

11.00R20-18
12.00R20-18



MG707 P20

10.00R20-18
11.00R20-18
12.00R20-18

ALL POSITION




MG117

Features

- Three zigzag grooves design with lugs. Provide excellent wet performance
- Special tread compound. Provide outstanding resistance to abrasion
- Shoulder design with lugs and sipes. Provide outstanding heat dissipation

Suitable for:

- All wheel position of truck.
- Ational highways and regional roads as well as on/off road condition.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
12R22.5	18	152/149	L	-	9.00	1085	300	16	TL	930/930	3550/2250



MG122

Features

- Versatile pattern provides good traction and stability for various road surfaces.
- Shoulder design minimizes heat build-up.

Suitable for:

- All wheel position of truck.
- National highways and regional roads as well as on/off road condition.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
12.00R24	20	180/157	K	-	8.50	1226	315	15.5	TT	900/900	4500/4125
315/80R22.5	20	156/152(154/153)	(LM)	M+S	9.00	1076	312	16.5	TL	860/860	4000/3550



MG307

Features

- Wide tread width and longitudinal rib pattern with large contact-area designed for drive control and long mileage.
- Special groove design prevents stone trapping and penetration resulting in groove cracks.

Suitable for:

- All wheel position of cargo truck, steer and trailer position of dump truck and concrete mixer.
- Regional roads and on/off road surfaces.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
10.00R20	18	149/146	K	-	7.50	1054	278	17	TT	930/930	3250/3000
11.00R20	18	152/149	K	-	8.00	1085	293	17.5	TT	930/930	3550/2250
12.00R20	18	154/149	J	-	8.50	1125	315	18	TT	840/770	3790/3270



MG702

Features

- Versatile pattern provides good traction and stability for various road surfaces.
- Shoulder design minimizes heat build-up.

Suitable for:

- All wheel position of truck.
- National highways and regional roads as well as on/off road condition.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
6.50R16	12	113/110	K	M+S	5.50F	750	185	11	TT	770/770	1110/1030
7.00R16	14	118/114	M	-	5.50F	775	200	14	TT	770/770	1330/1180
7.50R16	14	122/118	M	-	6.00F	805	215	13	TT	740/740	1495/1310
8.25R16	16	128/124	M	-	6.50H	855	235	15	TT	770/770	1800/1600
8.25R20	16	130/137	L	-	6.50	971	232	13.5	TT	930/930	2430/2100
9.00R20	16	144/142	K	-	7.00	1019	259	15.5	TT	900/900	2800/2550
10.00R20	18	149/146	K	-	7.50	1055	278	16.5	TT	930/930	3250/3000
11.00R20	18	152/149	K	-	8.00	1085	293	17	TT	930/930	3550/3250
12.00R20	18	154/149	K	-	8.50	1125	315	17.5	TT	840/770	3790/3270
12.00R24	20	160/157	K	-	8.50	1225	315	16	TT	930/930	4500/4125
11R22.5	16	148/145	M	M+S	8.25	1054	279	15	TL	830/830	3000/2725
12R22.5	18	152/149	M	M+S	9.00	1085	300	16	TL	930/930	3550/3250
13R22.5	20	156/152(154/153)	(LM)	M+S	9.75	1124	320	16	TL	960/960	4000/3550

Tire Direct

La nueva generación

ALL POSITION **MIRAGE**



MG708

Features

- Anti-abrasion tread compound for better mileage and enhanced wear resistance.
- Shoulder design minimizes heat build-up.

Suitable for:

- All wheel position of cargo truck for medium and long distance.
- Regional roads.

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kPa) (single/dual)	MAX LOAD (kg) (single/dual)
9.00R20	16	144/142	K	-	7.00	1019	259	15.0	TT	900/900	2800/2650
10.00R20	18	149/146	K	-	7.50	1055	278	16.5	TT	930/930	3250/3000
11.00R20	18	152/149	K	-	8.00	1085	295	17.0	TT	930/930	3550/3250
12.00R20	18	154/149	K	-	8.50	1125	315	17.5	TT	840/770	3700/3270



ST011

Features

- Versatile pattern provides good traction and stability for various road surfaces.
- Shoulder design minimizes heat build-up.

Suitable for:

- Drive and Trailer position of cargo trucks.
- National highways and regional roads as well as on/off road condition.

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kPa) (single/dual)	MAX LOAD (kg) (single/dual)
315/80R22.5	20	156/152	L	M+S	9.00	1076	312	16.5	TL	860/860	4000/3550

MIRAGE ALL POSITION



FAR515

Features

- Special tread compound Provide outstanding resistance to abrasion
- Three zigzag grooves Provide good applicability for all position
- Special groove design Deliver stone-ejecting property
- Optimized pattern design Provide outstanding resistance to irregular abrasion

Suitable for:

- All wheel position of truck.
- Ational highways and regional roads as well as on/off road condition.

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kPa) (single/dual)	MAX LOAD (kg) (single/dual)
11R22.5	14	144/142	M	M+S	8.25	1054	279	15.5	TL	720/720	2800/2650
11R22.5	16	148/145	L	M+S	8.25	1054	279	15.5	TL	850/850	3150/2800
12R22.5	18	152/149	L	M+S	9.00	1085	298	16.5	TL	930/930	3550/3250
295/80R22.5	18	152/149	M	M+S	9.00	1044	298	16.0	TL	900/900	3550/3250
315/80R22.5	20	156/152	K	M+S	9.00	1076	312	16.5	TL	860/860	4000/3550

Features

- Three zigzag grooves Provide excellent anti-side slipping performance and ensure excellent water evacuation
- Combination of rib and lug design Deliver outstanding traction and handling
- Shoulder design with lugs Provide excellent heat dissipation

Suitable for:

- All wheel position of truck.
- Ational highways and regional roads as well as on/off road condition.



FAM517

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kPa) (single/dual)	MAX LOAD (kg) (single/dual)
11R22.5	16	148/143	K	M+S	8.25	1054	279	15.5	TL	850/850	3150/2800
12R22.5	18	152/149	K	M+S	9.00	1085	298	16	TL	930/930	3550/3250
295/80R22.5	18	152/149	K	M+S	9.00	1044	298	16	TL	900/900	3550/3250
315/80R22.5	20	156/152	K	M+S	9.00	1076	312	17	TL	860/860	4000/3550
12.00R24	20	160/157	K	M+S	8.50	1225	315	17	TL	900/900	4500/4125

STEER AND TRAILER



MG111

Features

- Solid rib design combined with multiple sipes.
- Four wide circumferential grooves.
- Solid shoulder design.

Suitable for:

- Provide excellent heat dissipation and improved regular wear with lower resistance
- Ensure excellent water evacuation, even pressure distribution and heat dissipation
- Provide outstanding resistance to abrasion.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (max/psi/bsa)	MAX LOAD (kg) (max/bsa)
11R22.5	16	146/141	L	M+S	8.25	1054	279	15	TL	830/830	3000/2725
11R24.5	16	146/141	M	-	8.25	1104	279	15	TL	720/720	3000/2725
11R24.5	16	149/146	L	-	8.25	1104	279	15	TL	720/720	3000/2725
285/75R24.5	14	144/141	M	-	8.25	1050	283	15.5	TL	760/760	3800/2575
285/75R24.5	16	147/144	L	-	8.25	1050	283	15.5	TL	830/830	3075/2800
295/75R22.5	14	144/141	M	-	9.00	1014	298	15.5	TL	760/760	2800/2575
295/75R22.5	16	146/143	L	-	9.00	1014	298	15.5	TL	830/830	3000/2725
315/75R17.5	16	135/133	J	M+S	6.00	767	212	12	TL	850/850	2180/2060
355/75R17.5	16	132/130	M	M+S	6.75	797	231	13	TL	875/875	2725/2575
275/70R19.5	14	128/126	L	-	6.75	811	226	13	TL	760/760	1800/1700
245/70R19.5	16	135/133	M	-	7.50	839	244	13	TL	830/830	2180/2060
255/70R22.5	16	140/137	L	-	7.50	930	255	15	TL	830/830	2500/2300




MG121

Features

- Steer position rib pattern provides directional control and low rolling resistance.
- Strong shoulder provides excellent handling.
- Small sipes on ribs and shoulders for better performance on wet surface, reduces heat buildup.
- Large contact area ensures long mileage.

Suitable for:

- Steer and trailer position of truck and all wheel position of bus.
- Highways and national roads.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (max/psi/bsa)	MAX LOAD (kg) (max/bsa)
9.25R16	16	128/124	M	-	6.50H	855	235	13.5	TT	770/770	1800/1600
9.5R17.5	16PR	143/141	J	-	6.75	842	172	13	TL	875/127	2725/2575
11.0R20	18	152/149	K	-	8.00	1085	293	15.5	TT	930/930	3550/3250
295/70R22.5	16	152/149	M	M+S	9.00	1044	298	16.5	TL	900/900	3550/3250
315/70R22.5	20	154/150(152/148)	LIM	M+S	9.00	1014	312	15.5	TL	850/850	3550/3150
315/70R22.5	20	156/152(154/151)	LIM	M+S	9.00	1076	312	15.5	TL	860/860	4000/3550

MIRAGE STEER AND TRAILER



MG123

Features

- Four circumferential grooves
Provide excellent anti-side slipping
- Solid shoulder design
Performance and ensure excellent water evacuation
- Specially designed compound
Provide outstanding resistance to abrasion

Suitable for:

- Steer and trailer position of truck, all wheel position of bus
- Highways, national roads and urban roads.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (max/psi/bsa)	MAX LOAD (kg) (max/bsa)
11.0R20	18	152/149	K	-	8.00	1085	293	16.5	TT	930/930	3550/3250

Features

- Solid rib design combined with multiple sipes
Provide excellent heat dissipation and improved regular wear with lower resistance
- Four wide circumferential grooves
Ensure excellent water evacuation, even pressure distribution and heat dissipation

Suitable for:

- Steer and trailer position of truck, all wheel position of bus.
- Highways, national roads and urban roads.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (max/psi/bsa)	MAX LOAD (kg) (max/bsa)
315/80R22.5	20	154/152(154/151)	LIM	M+S	9.00	1076	312	15.5	TL	860/860	4000/3550

Tire Direct

La nueva generación

STEER AND TRAILER **MIRAGE**



MG330

Features

- New tread pattern and compound for lower rolling resistance and wear-rate, improving on fuel consumption and mileage.
- Special groove design to prevent stone trapping in grooves.
- Lateral sipes for more even wear and better wet grip.

Suitable for:

- Steer and trailer position of truck. All wheel position of bus.
- Highways, national roads and urban with good road surfaces.

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
11R22.5	16	148/145	M	M+S	8.25	1054	279	15	TL	830/830	3150/2900
12R22.5	18	152/149	M	M+S	9.00	1085	300	16.5	TL	930/930	3550/3250



MG606/606+

Features

- Good directional handling with four longitudinal grooves.
- Rib design with zigzag sipes provides excellent lateral traction and wet grip.

Suitable for:

- Steer and trailer position of cargo truck and all wheel position of bus.
- Highway, regional roads and urban driving condition.

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
9.00R20	16	144/142	K	-	7.00	1019	259	15.0	TL	900/900	2800/2650
10.00R20	18	149/146	K	-	7.50	1055	278	15.0	TL	930/930	3150/3000
11.00R20	18	152/149	K	-	8.00	1085	298	17.0	TL	930/930	3550/3250
12.00R20	18	154/149	K	-	8.50	1125	315	17.5	TL	840/770	3780/3270
11R22.5	16	148/145	M	M+S	8.25	1054	279	15.0	TL	830/830	3150/2900
11R22.5	20	156/152	L	M+S	9.00	1076	312	14.5	TL	860/860	4000/3550

MIRAGE STEER AND TRAILER



MG607

Features

- Large footprint for better traction and stability.
- Abrasion-resistant tread compound for better mileage and reduced wear-rate.

Suitable for:

- Drive position of cargo truck traveling at mid to long distance.
- Highway and regional roads.

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
12.00R24	20	166/157	K	-	8.50	1225	315	20.0	TT	900/900	4500/4125



MG660

Features

- New tread pattern and compound for lower rolling resistance and wear-rate, reducing fuel consumption and improving usage mileage.
- Lateral sipes for more even wear and better wet grip.

Suitable for:

- Steer and trailer position of truck, all wheel position of bus.
- Highways, national roads and urban roads.

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
11R22.5	16	148/145	M	M+S	8.25	1054	279	15.0	TL	830/830	3150/2900
12R22.5	18	152/149	M	-	9.00	1085	300	16.5	TL	930/930	3550/3250
11R22.5	20	156/152/154/151	LIM	M+S	9.75	1124	330	17.0	TL	860/860	4000/3550
215/75R17.5	16	135/133	J	M+S	6.00	767	212	12.0	TL	850/850	2180/2060
255/70R22.5	16	146/137	L	-	7.50	930	255	14.0	TL	830/830	2500/1300
295/80R22.5	18	152/149	M	M+S	9.00	1044	298	15.0	TL	900/900	3550/3250
315/70R22.5	20	154/150/152/148	LIM	M+S	9.90	1014	312	15.0	TL	900/900	3750/3350
315/80R22.5	20	156/152/154/151	LIM	M+S	9.90	1076	312	14.5	TL	860/860	4000/3550

Tire Direct

La nueva generación

STEER AND TRAILER **MIRAGE**



MG688

Features

- Longitudinal rib pattern for directional control and low rolling resistance compound for reduced fuel consumption.
- Small sipes on ribs and shoulders for more even wear and reduce heat build-up.

Suitable for:

- Steer and trailer position of truck.
- Highways and national roads.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kPa) (single/dual)	MAX LOAD (kg) (single/dual)
295/80R22.5	18	152/149	M	M+S	9.00	1044	298	15.0	TL	850/850	3550/3150



FAR518

Features

- Special tread compound
Provide outstanding resistance to abrasion
- Three zigzag grooves
Provide good applicability for all position
- Special groove design
Deliver stone-ejecting property

Suitable for:

- Steer and trailer position of truck, all wheel position of bus.
- Highways, national roads and urban roads.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kPa) (single/dual)	MAX LOAD (kg) (single/dual)
225/70R17.5	14	129/127	M	M+S	6.75	783	226	13.0	TL	725/725	1850/1750
245/70R17.5	16	136/134	M	M+S	7.50	789	248	13.0	TL	850/850	2240/2120
245/70R17.5	18	143/141(146/144)	HP	M+S	7.50	789	248	13.0	TL	875/875	2725/2575
245/70R18.5	16	136/134	M	M+S	7.50	819	248	14.0	TL	825/825	2240/2120
245/70R18.5	18	143/140	J	M+S	7.50	819	248	14.0	TL	850/850	2575/2500
265/70R18.5	16	140/138	M	M+S	7.50	867	262	14.0	TL	775/775	2500/2300
265/70R18.5	18	143/141	J	M+S	7.50	867	262	14.0	TL	850/850	2725/2575
285/70R19.5	16	146/144(144/142)	LOM	M+S	8.25	895	283	14.0	TL	850/850	3000/2800
285/70R19.5	18	150/148	J	M+S	8.25	895	283	14.0	TL	900/900	3350/3150

DRIVE



MG303

Features

- Unique inter-connected block design with longitudinal grooves provide drive stability, more even tread wear and better resistance to tearing.
- Beads are reinforced for heavier load.
- Large pattern blocks for better traction and braking.
- Self-cleaning grooves for mud and sand surfaces.

Suitable for:

- Drive and trailer position of dump truck, mining truck and concrete mixer.
- Off road or loose surface condition including construction and mining sites, with a maximum speed of 60km/h.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kPa) (single/dual)	MAX LOAD (kg) (single/dual)
7.00R16LT	14	118/114	K	-	5.50	775	200	14	TT	770/770	1320/1180
7.50R16LT	14	122/118	J	-	6.00	805	215	15	TT	770/770	1500/1320
8.25R16LT	16	126/124	J	-	6.50	855	235	16	TT	770/770	1800/1600
8.25R20	16	139/137	K	-	6.50	874	236	16	TT	930/930	2430/2300
9.00R20	16	144/142	J	-	7.00	1019	259	17	TT	790/790	2575/2430
10.00R20	18	149/146	K	-	7.50	1054	278	18	TT	930/930	3250/3000
11.00R20	18	152/149	J	-	8.00	1095	293	19	TT	930/930	3550/3250
12.00R20	18	154/149	K	-	8.50	1125	315	20	TT	840/770	3790/3270



MG312

Features

- Block pattern design
- Solid shoulder design
- Four wide circumferential grooves

Suitable for:

- Provide excellent driving and braking force
- Provide outstanding resistance to abrasion
- Ensure excellent water evacuation even pressure distribution and heat dissipation.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kPa) (single/dual)	MAX LOAD (kg) (single/dual)
11R22.5	16	146/143	L	M+S	8.25	1054	279	21.5	TL	830/830	3000/2725
11R24.5	16	146/143	M	-	8.25	1104	279	21.5	TL	720/720	3000/2725
11R24.5	16	149/146	L	-	8.25	1104	279	21.5	TL	830/830	3250/3000
285/75R24.5	14	144/141	M	-	8.25	1056	283	22.0	TL	760/760	2800/2575
285/75R24.5	16	147/144	L	-	8.25	1056	283	22.0	TL	830/830	3075/2800
295/75R22.5	14	144/141	M	-	9.00	1020	298	22.0	TL	760/760	2800/2575
295/75R22.5	16	146/143	L	-	9.00	1014	298	22.0	TL	830/830	3000/2725

Tire Direct

La nueva generación

DRIVE MIRAGE



MG6313

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (max psi)	MAX LOAD (kg) (max lbs)
7.50R16	14	122/118	M	-	6.00G	805	215	15	TT	770/770	1500/1320
8.25R16	16	128/124	M	-	6.50H	855	235	16	TT	740/740	1800/1600
8.25R20	16	139/137	K	-	6.50	974	236	16	TT	930/930	2430/2390
9.00R20	16	144/142	K	-	7.00	1019	259	17	TT	790/790	2174/2410
10.00R20	18	149/146	K	-	7.50	1054	278	18	TT	930/930	3250/3090
11.00R20	18	152/149	K	-	8.00	1085	293	19	TT	930/930	3350/3250
12.00R20	18	154/149	K	-	8.50	1125	315	20	TT	840/770	3790/3270

Features

- Lug and block pattern design improves traction, driving and braking performance.
- Special groove design prevents stone picking.
- Special tread compound provides outstanding resistance to puncture and tearing.
- Open shoulder provides excellent heat dissipation.

Suitable for:

- Drive position of dump truck, mining truck and concrete mixer.
- Off road or loose surface condition including construction and mining sites.



MG505

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (max psi)	MAX LOAD (kg) (max lbs)
10.00R20	18	148/146	K	-	7.50	1054	278	20.5	TT	930/930	3250/3090

Features

- Block pattern design Provide excellent driving and braking force
- Extra wide footprint Enhanced stability and resistance to abrasion
- Deeper tread depth design Improved mileage performance

Suitable for:

- Drive position of truck.
- Highways and national roads.



MG322

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (max psi)	MAX LOAD (kg) (max lbs)
12.00R24	20	146/157	K	-	8.50	1226	315	18.9	TT	900/900	4000/4125
315/80R22.5	20	156/152	L	M+S	9.00	1076	312	20.5	TL	860/860	4500/5550

Features

- Special tread compound. Provide outstanding resistance to puncture and tearing
- Lug and special block pattern design Improved traction, driving and braking performance

Suitable for:

- Drive and trailer position of dump truck, mining truck and concrete mixer.
- Off road condition including construction and mining sites.



MG628

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (max psi)	MAX LOAD (kg) (max lbs)	
13R22.5	16	148/145	(146/146)	K	M+S	8.25	1054	279	16.5	TL	830/770	3000/2750
12R22.5	18	152/149	L	-	9.00	1085	300	17.5	TL	930/930	3550/3250	
13R22.5	20	156/152/154/151	(151)	M+S	9.75	1124	320	18.0	TL	860/860	4000/3550	
215/70R17.5	16	126/133	J	M+S	6.00	787	212	14.0	TL	850/850	2180/2060	
235/75R17.5	16	149/144	J	M+S	6.75	797	233	15.0	TL	875/875	2725/2375	
295/80R22.5	18	152/148	M	M+S	9.00	1044	298	16.0	TL	860/860	3550/3150	
315/70R22.5	20	156/150/152/148	(148)	M+S	9.00	1014	312	21.0	TL	900/900	3750/3350	
315/80R22.5	20	156/153/154/150	(150)	M+S	9.00	1076	312	20.0	TL	860/860	4000/3550	

Features

- A drive position pattern with block design that provides grip, traction and stability.
- Wider tread width and larger contact area especially at shoulder area for longer mileage and even-wear.

Suitable for:

- Drive position of truck.
- Highways and national roads.

Tire Direct

La nueva generación

DRIVE MIRAGE



MG638/MG638+

Features

- Block pattern designed for drive position providing first-class performance on grip, traction and stability.
- Wider tread width for longer mileage and even-wear.

Suitable for:

- Drive position of truck.
- Highways and national roads.

*638+ is designed with deeper tread depth.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (min/max/ideal)	MAX LOAD (kg) (min/max/ideal)
10.0R20	18	148/146	K	-	7.50	1054	278	23	TT	930/930	3250/3000
11R22.5	16	148/148	M	M+S	8.25	1054	279	20	TL	850/850	3150/2900
12R22.5	18	152/149	M	M+S	9.00	1085	300	16	TL	930/930	3550/3250
12R22.5	18	152/149	M	M+S	9.00	1085	300	20	TL	930/930	3550/3250
315/70R22.5	20	156/152/154/152	LIM	M+S	9.00	1014	312	20	TL	900/900	3750/3350
315/80R22.5	20	154/150/152/148	LIM	M+S	9.00	1076	321	23	TL	860/860	4000/3550



MG900/MG668

Features

- Block pattern designed for drive position providing first-class performance on grip, traction and stability.
- Wider tread width with inter-linked blocks for longer mileage and even wear.

Suitable for:

- Drive position of truck.
- Highways and national roads.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (min/max/ideal)	MAX LOAD (kg) (min/max/ideal)
10.0R20	18	148/146	K	-	7.50	1055	278	21.9	TT	930/930	3250/3000
295/80R22.5	18	152/149	M	M+S	9.00	1044	298	18.0	TL	860/860	3550/3150

MIRAGE DRIVE



MG701

Features

- A mixed rig and lug pattern with large center elements for enhanced directional stability.
- Lateral grooves maximize traction on different road surfaces.

Suitable for:

- Drive position of truck, drive and trailer position of concrete mixer and dump truck.
- National highway and regional roads as well as on/off road condition.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (min/max/ideal)	MAX LOAD (kg) (min/max/ideal)
9.0R20	16	144/142	J	-	7.00	1019	259	16.5	TT	900/900	2800/2650
10.0R20	18	148/146	K	-	7.50	1054	278	17	TT	930/930	3250/3000
11.0R20	18	152/149	K	-	8.00	1085	293	18	TT	930/930	3550/3250
12.0R20	18	154/149	K	-	8.50	1125	315	19	TT	840/770	3790/3270
12R22.5	18	152/149	M	M+S	9.00	1085	300	18.5	TL	930/930	3550/3250



MG706

Features

- Large lateral block pattern maximizes traction in muddy road condition.
- Special tread compound for better resistance to shipping and cutting.

Suitable for:

- Drive position of cargo truck for medium and short distance.
- Drive and trailer position of dump truck and concrete mixer.
- Regional roads, unpaved roads as well as construction and mining sites.



TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (min/max/ideal)	MAX LOAD (kg) (min/max/ideal)
7.00R16	14	118/114	M	-	5.50R	775	200	12.0	TT	770/770	1320/1180
7.50R16	14	122/118	M	-	6.00R	805	215	14.0	TT	740/740	1495/1310
8.25R16	16	128/124	M	-	6.50H	855	235	15.0	TT	740/740	1800/1600
8.25R20	16	130/137	K	-	6.50	874	216	16.0	TT	930/930	2450/2100
9.0R20	16	144/142	K	-	7.00	1019	259	16.0	TT	900/900	2800/2650
10.0R20	18	148/146	K	-	7.50	1055	278	16.5	TT	930/930	3250/3000
11.0R20	18	152/149	K	-	8.00	1085	293	17.5	TT	930/930	3550/3250
12.0R20	18	154/149	K	-	8.50	1125	315	18.5	TT	840/770	3790/3270

Tire Direct

La nueva generación

DRIVE MIRAGE



MG729

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
10.00R20	18	149/146	K	-	7.50	1055	278	21.0	TT	930/930	3250/3900
11.00R20	18	152/149	K	-	8.00	1085	293	18.0	TT	930/930	3550/3250
12.00R20	18	154/148	K	-	8.50	1125	315	18.5	TT	840/770	3790/3270
12.00R24	20	160/157	K	-	8.50	1225	315	19.0	TT	930/930	4500/4125

Features

- Unique inter-connected block design with longitudinal grooves provide drive stability, more even tread wear and better resistance to tearing.
- Beads are reinforced for heavier load.
- Large pattern blocks for better traction and braking.
- Self-cleaning grooves for mud and sand surfaces.

Suitable for:

- Drive and trailer position of dump truck, mining truck and concrete mixer.
- Off road or loose surface condition including construction and mining sites, with a maximum speed of 60km/h.



FTL311

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
385/65R22.5	20	160(158)	K/L	M+S	12.25	996	386	15.5	TL	900	4500
385/60R22.5	20	160(158)	K/L	M+S	11.75	1072	389	16	TL	900	4500
420/60R22.5	20	165	K	M+S	13	1124	430	16	TL	825	5100
465/60R22.5	20	169	K	M+S	13	1150	444	16	TL	900	5800

Features

- Optimized pattern design Provide outstanding resistance to irregular
- Special groove design Deliver stone-ejecting property
- Specially designed compound Deliver lower rolling resistance

Suitable for:

- Trailer position of truck, all wheel position of bus.
- Highways, national roads and urban roads.



MG768

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
10.00R20	18	149/146	K	-	7.50	1055	278	18	TT	930/930	3250/3900
11.00R20	18	152/149	J	-	8.00	1085	293	18	TT	930/930	3550/3250
12.00R20	18	154/148	K	-	8.50	1125	315	20	TT	840/770	3790/3270
12R22.5	18	152/149	M	-	9.00	1085	300	20	TL	930/930	3550/3250
13R22.5	20	156(152/146/131)	LM	M+S	9.75	1124	320	20	TL	870/875	4000/3950
11.5/60R22.5	20	156(152/146/131)	LM	M+S	9.00	1076	312	20	TL	865/860	4000/3550

Features

- Innovative tread design and compounds promote excellent traction and resist uneven wear.
- Durable casing construction perfect for tough regional and urban use.
- Deep tread depth provides maximum tread life.

Suitable for:

- Drive and trailer position of dump truck, mining truck and concrete mixer.
- Off road condition including construction and mining sites.



FTM313

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
385/65R22.5	20	160(158)	K/L	M+S	11.75	1072	389	16.5	TL	900	4500

Features

- Special tread compound Provide outstanding resistance to puncture and tearing
- Lug and block pattern design Improved traction, driving and braking performance
- Special groove design Improve stone-ejecting property

Suitable for:

- Drive position of truck.
- Highways and national roads.

Tire Direct

La nueva generación

TRAILER MIRAGE



MG618

Features

- Low rolling resistance for reduced fuel consumption.
- Lateral grooves on ribs for better traction.
- Longitudinal grooves on shoulder for even wear.

Suitable for:

- Trailer position of truck.
- Highways, national roads, harbors and ports.

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
18R22.5	16	146/142	M	M+S	8.25	1054	278	11.5	TL	850/850	3150/2900
12R22.5	18	152/149	M	-	9.00	1085	300	12.5	TL	930/930	3550/3250
295/75R22.5	14	144/141	M	M+S	9.00	1014	298	11.0	TL	760/760	2800/2575
295/75R22.5	16	146/143	L	M+S	9.00	1014	298	11.0	TL	830/830	3000/2725



ST022

Features

- Tread compound for better mileage.
- Tread designed for even wear.

Suitable for:

- Trailer position of truck traveling mid to long distance.
- National highways and regional roads.

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
235/75R17.5	16	145/141	J	M+S	6.75	787	233	13	TL	875/875	2725/2575
35LXSR22.5	20	300	K	M+S	11.75	1072	389	17	TL	900/-	4500/-

OFF THE ROAD



MG168

Features

- Special tread compound
- Provide outstanding resistance to puncture and tearing
- Lug and block pattern design
- Improved traction, driving and braking performance

Suitable for:

- Drive and trailer position of dump truck, mining truck and concrete mixer.
- Off road or loose surface condition including construction and mining sites with vehicle traveling at less than 60 km per hour.

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
700R16	14	118/114	K	-	5.50F	775	200	17.5	TT	770/770	1320/1180
750R16	14	122/118	K	-	6.00G	805	215	18	TT	770/770	1500/1320
820R16	16	126/124	J	-	6.50H	855	235	18	TT	770/770	1800/1600
820R20	16	139/137	C	-	6.50	974	236	21	TT	930/930	2430/2300
900R20	16	144/142	C	-	7.00	1019	259	21.5	TT	790/790	2575/2430
1000R20	18	149/146	C	-	7.50	1019	278	22	TT	930/930	3250/3000



MG318

Features

- Large lateral blocks provides excellent traction and grip.
- Special tread compound for improved resistance to tearing and chipping.
- Reinforced bead area for better load capacity.

Suitable for:

- Drive and trailer position of dump truck, mining truck and concrete mixer.
- Off road or loose surf ace condition including construction and mining sites with vehicle traveling at less than 60 km per hour.

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
8.25R20	16	130/127	C	-	6.50	974	236	16	TT	930/930	2430/2300
9.00R20	16	144/142	C	-	7.00	1019	259	17	TT	790/790	2575/2430
10.00R20	18	149/146	C	-	7.50	1054	278	18	TT	930/930	3250/3000
11.00R20	18	152/149	C	-	7.50	1096	293	24	TT	930/930	3550/3250
12.00R20	18	154/149	C	-	8.00	1125	315	25	TT	860/790	3760/3270
12.00R24	20	160/157	K	-	8.50	1225	315	21.5	TL	930/930	4500/4125
295/80R22.5	18	152/149	C	M+S	9.00	1044	298	21.5	TL	900/900	3550/3250

Tire Direct

La nueva generación

OFF THE
ROAD

MIRAGE



MG320

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
295/80R22.5	18	152/149	C	M+S	9.00	1044	288	21.5	TL	900/900	3550/3250

Features

- Special tread compound Lug and block pattern design Provide outstanding resistance to puncture and tearing
- Reinforced carcass and bead design Improved traction, driving and braking performance.

Suitable for:

- Drive and trailer position of dump truck, mining truck and concrete mixer .
- Off road or loose surface condition including construction and mining sites with vehicle traveling at less than 60 km per hour.



MG321

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
11.00R20	18	151/149	C	-	8.00	1096	293	24	TT	930/930	3550/3250
12.00R20	18	154/149	K	-	8.50	1116	315	25	TT	840/770	3790/3270

Features

- Lug and block pattern design Improved traction, driving and braking performance
- Special tread compound reinforced carcass and bead design. Provide outstanding resistance to puncture and tearing.

Suitable for:

- Drive and trailer position of dump truck, mining truck and concrete mixer .
- Off road or loose surface condition including construction and mining sites with vehicle traveling at less than 60 km per hour.

MIRAGE

OFF THE
ROAD



MG707

Features

- Special tread compound for better resistance to chipping and cutting.
- Large block pattern maximizes traction in uneven and muddy terrain.
- Reinforced bead and casing for better load capacity and multiple retread.

Suitable for:

- Drive and trailer position of dump truck and concrete mixer.
- Regional roads, unpaved roads as well as construction and mining sites.

TYRE SIZE	PLY RATING	LOAD INDEX	SPEED SYMBOL	M+S	RIM	OVERALL DIAMETER (mm)	SECTION WIDTH (mm)	TREAD DEPTH (mm)	TUBE	MAX PRESSURE (kpa) (single/dual)	MAX LOAD (kg) (single/dual)
10.00R20	18	149/146	K	-	7.50	1065	278	20.5	TT	830/830	3000/2725
11.00R20	18	152/149	K	-	8.00	1095	293	21.0	TT	830/830	3350/3075
12.00R20	18	154/149	K	-	8.50	1115	315	21.5	TT	840/770	3730/3270

Tire Direct

La nueva generación

OFF THE
ROAD

MIRAGE



MG826

SIZE	PR	LOAD INDEX SPEED RATING	MAX LOAD (kg)	MAX LOAD (lbs)	MAX PRESSURE (kpa)	MAX PRESSURE (psi)	OUTER DIAMETER	SECTION WIDTH	TREAD DEPTH	TREAD WIDTH
11R22.5-18	18	149/146L	3250/3000	7160/6610	830/830	135/135	1054	279	22.5	213
11R24.5-18	18	152/149K	3550/3250	7830/7160	830/830	135/135	1104	279	26.5	214



MG603xs

SIZE	PR	LOAD INDEX SPEED RATING	MAX LOAD (kg)	MAX LOAD (lbs)	MAX PRESSURE (kpa)	MAX PRESSURE (psi)	OUTER DIAMETER	SECTION WIDTH	TREAD DEPTH	TREAD WIDTH
11R22.5-18	18	149/146L	3000/2725	6610/6005	830/830	120/120	1054	279	13.5	210



MG617xs

SIZE	PR	LOAD INDEX SPEED RATING	MAX LOAD (kg)	MAX LOAD (lbs)	MAX PRESSURE (kpa)	MAX PRESSURE (psi)	OUTER DIAMETER	SECTION WIDTH	TREAD DEPTH	TREAD WIDTH
11R22.5-18	18	149/146L	3000/2725	6610/6005	830/830	120/120	1054	279	13.5	202

MIRAGE

OFF THE
ROAD

MIRAGE

18
CAPAS

Tire Direct
La nueva generación

MIRAGE

18
CAPAS

MG111



MEDIDA	MODELO	TIPO	CAPAS
11R22.5	MG111	DIRECCIÓN	18
11R24.5	MG111	DIRECCIÓN	18

MG312



MEDIDA	MODELO	TIPO	CAPAS
11R22.5	MG312	TRACCIÓN	18
11R24.5	MG312	TRACCIÓN	18

Tire Direct
La nueva generación

MIRAGE

18
CAPAS

MG826



MEDIDA	MODELO	TIPO	CAPAS
11R22.5	MG826	MINERA	18
11R24.5	MG826	MINERA	18

MG702



MEDIDA	MODELO	TIPO	CAPAS
11R22.5	MG702	SERVICIO MIXTO	18
11R24.5	MG702	SERVICIO MIXTO	18

Tire Direct
La nueva generación

Technical File

SIZE	PLY RATING	LOAD INDEX	SPEED RATING	PATTERN	M+S	TUBE	STANDARD RIM	MAX LOAD STD SINGLE	MAX LOAD STD DUAL	MAX PRESSURE STD SINGLE	MAX PRESSURE STD DUAL	THREAD DEPTH (mm)	SECTION WIDTH (mm)	OUTER DIAMETER (mm)
6.50R16	12	131/10	K	HF702	-	TT	5.50F	1150	1030	770	770	11.0	185	750
7.00R16	14	118/114	K	HF168	-	TT	5.50F	1320	1180	770	770	17.5	200	775
7.00R16	14	118/114	M	HF702	-	TT	5.50F	1320	1180	770	770	14.0	200	775
7.00R16	14	118/114	K	HF303	-	TT	5.50F	1320	1180	770	770	14.0	200	775
7.00R16	14	118/114	M	HF706	-	TT	5.50F	1320	1180	770	770	12.0	200	775
7.50R16	14	122/118	K	HF168	-	TT	6.00G	1500	1320	770	770	18	215	805
7.50R16	14	122/118	M	HF702	-	TT	6.00G	1500	1320	770	770	13.0	215	805
7.50R16	14	122/118	J	HF303	-	TT	6.00G	1500	1320	770	770	15.0	215	805
7.50R16	14	122/118	M	HF706	-	TT	6.00G	1500	1320	770	770	14.0	215	805
7.50R16	14	122/118	M	HF313	-	TT	6.00G	1500	1320	770	770	15.0	215	805
8.25R16	16	128/124	M	HF121	-	TT	6.50H	1800	1600	770	770	13.5	235	855
8.25R16	16	128/124	J	HF168	-	TT	6.50H	1800	1600	770	770	18.0	235	855
8.25R16	16	128/124	M	HF702	-	TT	6.50H	1800	1600	770	770	15.0	235	855
8.25R16	16	128/124	J	HF303	-	TT	6.50H	1800	1600	770	770	18.0	235	855
8.25R16	16	128/124	L	HF706	-	TT	6.50H	1800	1600	740	740	15.0	235	855
8.25R16	16	128/124	M	HF313	-	TT	6.50H	1800	1600	740	740	16.0	235	855
8.25R20	16	139/137	C	HF168	-	TT	6.5	2430	2300	930	930	21.0	236	974
8.25R20	16	139/137	L	HF702	-	TT	6.5	2430	2300	930	930	13.5	236	974
8.25R20	16	139/137	K	HF303	-	TT	6.5	2430	2300	930	930	16.0	236	974
8.25R20	16	139/137	L	HF706	-	TT	6.5	2430	2300	930	930	14.5	236	974
8.25R20	16	139/137	C	HF318	-	TT	6.5	2430	2300	930	930	16.0	236	974
9.00R20	16	144/142	K	HF606	-	TT	7.00	2800	2650	900	900	15.0	259	1019
9.00R20	16	144/142	K	HF708	-	TT	7.00	2800	2650	900	900	15.0	259	1019
9.00R20	16	144/142	C	HF168	-	TT	7.00	2575	2430	790	790	21.5	259	1019
9.00R20	16	144/142	K	HF702	-	TT	7.00	2800	2650	900	900	15.5	259	1019
9.00R20	16	144/142	J	HF303	-	TT	7.00	2575	2430	790	790	17.0	259	1019
9.00R20	16	144/142	K	HF706	-	TT	7.00	2800	2650	900	900	18.0	259	1019
9.00R20	16	144/142	J	HF701	-	TT	7.00	2800	2650	900	900	18.5	259	1019
9.00R20	16	144/142	K	HF313	-	TT	7.00	2575	2430	790	790	17.0	259	1019
10.00R20	18	149/146	K	HF606	-	TT	7.5	3250	3000	930	930	15.0	278	1054
10.00R20	18	149/146	K	HF708	-	TT	7.5	3250	3000	930	930	16.5	278	1054
10.00R20	18	149/146	C	HF168	-	TT	7.5	3250	3000	930	930	22.0	278	1054
10.00R20	18	149/146	K	HF702	-	TT	7.5	3250	3000	930	930	16.5	278	1054
10.00R20	18	149/146	K	HF702N	-	TT	7.5	3250	3000	930	930	16.5	278	1054
10.00R20	18	149/146	K	HF706	-	TT	7.5	3250	3000	930	930	18.0	278	1054
10.00R20	18	149/146	K	HF303	-	TT	7.5	3250	3000	930	930	18.0	278	1054
10.00R20	18	149/146	K	HF706	-	TT	7.5	3250	3000	930	930	16.5	278	1054
10.00R20	18	149/146	K	HF307	-	TT	7.5	3250	3000	930	930	17.0	278	1054
10.00R20	18	149/146	K	HF638	-	TT	7.5	3250	3000	930	930	23.0	278	1054
10.00R20	18	149/146	K	HF701	-	TT	7.5	3250	3000	930	930	17.0	278	1054
10.00R20	18	149/146	K	HF313	-	TT	7.5	3250	3000	930	930	18.0	278	1054
10.00R20	18	149/146	K	HF707	-	TT	7.5	3250	3000	930	930	20.5	278	1054
10.00R20	18	149/146	C	HF318	-	TT	7.5	3250	3000	930	930	18.0	278	1054
10.00R20	18	149/146	K	HF729	-	TT	7.5	3250	3000	930	930	21.0	278	1054
10.00R20	18	149/146	K	HF668	-	TT	7.5	3250	3000	930	930	21.0	278	1054
10.00R20	18	149/146	K	HF505	-	TT	7.5	3250	3000	930	930	20.5	278	1054

Technical File

SIZE	PLY RATING	LOAD INDEX	SPEED RATING	PATTERN	M+S	TUBE	STANDARD RIM	MAX LOAD STD SINGLE	MAX LOAD STD DUAL	MAX PRESSURE STD SINGLE	MAX PRESSURE STD DUAL	THREAD DEPTH (mm)	SECTION WIDTH (mm)	OUTER DIAMETER (mm)
11.00R20	18	152/149	K	HF606	-	TT	8.00	3550	3250	930	930	17.0	293	1085
11.00R20	18	152/149	K	HF708	-	TT	8.00	3550	3250	930	930	17.0	293	1085
11.00R20	18	152/149	K	HF121	-	TT	8.00	3550	3250	930	930	15.5	293	1085
11.00R20	18	152/149	K	HF123	-	TT	8.00	3550	3250	930	930	16.5	293	1085
11.00R20	18	152/149	K	HF702	-	TT	8.00	3550	3250	930	930	17.0	293	1085
11.00R20	18	152/149	J	HF768	-	TT	8.00	3550	3250	930	930	18.0	293	1085
11.00R20	18	152/149	J	HF303	-	TT	8.00	3550	3250	930	930	19.0	293	1085
11.00R20	18	152/149	K	HF706	-	TT	8.00	3550	3250	930	930	17.5	293	1085
11.00R20	18	152/149	K	HF307	-	TT	8.00	3550	3250	930	930	17.5	293	1085
11.00R20	18	152/149	K	HF701	-	TT	8.00	3550	3250	930	930	18.0	293	1085
11.00R20	18	152/149	K	HF313	-	TT	8.00	3550	3250	930	930	19.0	293	1085
11.00R20	18	152/149	K	HF707	-	TT	8.00	3550	3250	930	930	21.0	293	1085
11.00R20	18	152/149	C	HF318	-	TT	8.00	3550	3250	930	930	24.0	293	1085
11.00R20	18	152/149	C	HF321	-	TT	8.00	3550	3250	930	930	24.0	293	1085
11.00R20	18	152/149	K	HF729	-	TT	8.00	3550	3250	930	930	18.0	293	1085
11.00R20	18	152/149	J	HF599H	-	TT	8.00	3550	3250	930	930	17.5	293	1085
11.00R20	18	152/149	J	HF929	-	TT	8.00	3550	3250	930	930	27.5	293	1085
12.00R20	18	154/149	K	HF606	-	TT	8.5	3790	3270	840	770	17.5	315	1125
12.00R20	18	154/149	K	HF708	-	TT	8.5	3790	3270	840	770	17.5	315	1125
12.00R20	18	154/149	K	HF702	-	TT	8.5	3790	3270	840	770	17.5	315	1125
12.00R20	18	154/149	K	HF768	-	TT	8.5	3790	3270	840	770	20.0	315	1125
12.00R20	18	154/149	K	HF303	-	TT	8.5	3790	3270	840	770	20.0	315	1125
12.00R20	18	154/149	K	HF706	-	TT	8.5	3790	3270	840	770	18.5	315	1125
12.00R20	18	154/149	K	HF307	-	TT	8.5	3790	3270	840	770	18.0	315	1125
12.00R20	18	154/149	K	HF701	-	TT	8.5	3790	3270	840	770	19.0	315	1125
12.00R20	18	154/149	K	HF313	-	TT	8.5	3790	3270	840	770	20.0	315	1125
12.00R20	18	154/149	K	HF707	-	TT	8.5	3790	3270	840	770	21.5	315	1136
12.00R20	18	154/149	K	HF318	-	TT	8.5	3790	3270	840	770	25.5	315	1125
12.00R20	18	154/149	K	HF321	-	TT	8.5	3790	3270	840	770	25.5	315	1136
12.00R20	18	154/149	K	HF729	-	TT	8.5	3790	3270	840	770	18.5	315	1125
12.00R24	20	160/157	K	HF122	-	TT	8.5	4500	4125	900	900	15.5	315	1125
12.00R24	20	160/157	K	HF702	-	TT	8.5	4500	4125	900	900	16.0	315	1125
12.00R24	20	160/157	K	HF607	-	TT	8.5	4500	4125	900	900	20.0	315	1125
12.00R24	20	160/157	K	HF322	-	TT	8.5	4500	4125	900	900	16.0	315	1125
12.00R24	20	160/157	K	HF729	-	TT	8.5	4500	4125	900	900	19.0	315	1125
12.00R24	20	160/157	K	SAM517	M+S	TT	8.5	4500	4125	900	900	17.0	315	1125
11R22.5	16	148/145	M	HF303	M+S	TL	8.25	3150	2900	850	850	15.0	279	1054
11R22.5	16	148/145	M	HF660	M+S	TL	8.25	3150	2900	850	850	15.0	279	1054
11R22.5	16	148/145	M	HF606	M+S	TL	8.25	3150	2900	850	850	15.0	279	1054
11R22.5	16	148/143	L	HF111	M+S	TL	8.25	3000	2725	830	830	15.0	279	1054
11R22.5	16	148/142	M	HF618	M+S	TL	8.25	3150	2900	850	850	11.5	279	1054
11R22.5	16	148/143	K	HF702	M+S	TL	8.25	3150	2900	850	850	15.0	279	1054
11R22.5	16	148/145	M	HF638	M+S	TL	8.25	3150	2900	850	850	20.0	279	1054
11R22.5	16	148/143	K	HF628	M+S	TL	8.25	3150	2900	850	850	16.5	279	1054
11R22.5	16	148/143	L	HF312	M+S	TL	8.25	3000	2725	830	830	21.5	279	1054
11R22.5	16	148/145	L	SAR515	M+S	TL	8.25	3150	2900	850	850	15.5	279	1054
11R22.5	16	148/143	K	SAM517	M+S	TL	8.25	3150	2900	850	850	15.5	279	1054
11R22.5	14	148/142	M	SAR515	M+S	TL	8.25	2800	2650	720	720	15.5	279	1054

Technical File

SIZE	PLY RATING	LOAD INDEX	SPEED RATING	PATTERN	M+S	TUBE	STANDARD ROLL	MAX LOAD (KG)		MAX PRESSURE (KPA)		TREAD DEPTH (mm)	SECTION WIDTH (mm)	OUTER DIAMETER (mm)	
								SINGLE	DUAL	SINGLE	DUAL				
11R24.5	14	146/143	M	HF111	-	TL	8.25	3000	2725	720	720	15.0	279	1104	
11R24.5	14	146/143	M	HF312	-	TL	8.25	3000	2725	720	720	21.5	279	1104	
11R24.5	16	146/143	L	HF111	-	TL	8.25	3000	2725	720	720	15.0	279	1104	
11R24.5	16	146/143	L	HF312	-	TL	8.25	3250	3000	830	830	21.5	279	1104	
	12R22.5	18	152/149	M	HF330	-	TL	9.00	3550	3250	930	930	16.5	300	1085
	12R22.5	18	152/149	M	HF660	-	TL	9.00	3550	3250	930	930	16.5	300	1085
	12R22.5	18	152/149	M	HF890	-	TL	9.00	3350	3250	930	930	16.5	300	1085
	12R22.5	18	152/149	L	HF117	-	TL	9.00	3550	3250	930	930	16.0	300	1085
	12R22.5	18	152/149	M	HF618	-	TL	9.00	3550	3250	930	930	12.5	300	1085
	12R22.5	18	152/149	L	HF702	M+S	TL	9.00	3550	3250	930	930	16.0	300	1085
	12R22.5	18	152/149	M	HF768	-	TL	9.00	3550	3250	930	930	20.0	300	1085
	12R22.5	18	152/149	L	HF307	-	TL	9.00	3550	3250	930	930	16.0	300	1085
	12R22.5	18	152/149	M	HF638	M+S	TL	9.00	3550	3250	930	930	16.0	300	1085
	12R22.5	18	152/149	M	HF638+	M+S	TL	9.00	3550	3250	930	930	20.0	300	1085
	12R22.5	18	152/149	L	HF628	-	TL	9.00	3550	3250	930	930	17.5	300	1085
	12R22.5	18	152/149	M	HF701	M+S	TL	9.00	3550	3250	930	930	18.5	300	1085
12R22.5	18	152/149	L	FARS15	M+S	TL	9.00	3550	3250	930	930	16.5	300	1085	
12R22.5	18	152/149	K	FARS17	M+S	TL	9.00	3550	3250	930	930	16.0	300	1085	
	13R22.5	20	156/152 (154/151)	L/M	HF660	M+S	TL	9.75	4000	3550	860	860	17.0	320	1124
	13R22.5	20	156/152 (154/151)	L/M	HF702	M+S	TL	9.75	4000	3550	860	860	16.5	320	1124
	13R22.5	20	156/152 (154/151)	L/M	HF768	M+S	TL	9.75	4000	3550	875	875	20.0	320	1124
	13R22.5	20	156/152 (154/151)	L/M	HF628	M+S	TL	9.75	4000	3550	860	860	18.0	320	1124
215/75R17.5	16	135/133	J	HF660	M+S	TL	6.00	2180	2060	850	850	12.0	212	767	
215/75R17.5	16	135/133	J	HF111	M+S	TL	6.00	2180	2060	850	850	12.0	212	767	
215/75R17.5	16	135/133	J	HF628	M+S	TL	6.00	2180	2060	850	850	12.0	212	767	
225/70R19.5	14	128/126	L	HF111	-	TL	6.75	1800	1700	760	760	13.0	226	811	
225/75R17.5	14	129/127	M	FARS18	M+S	TL	6.75	1800	1750	725	725	13.0	226	783	
225/75R17.5	16	143/141	J	ST022	M+S	TL	6.75	2725	2575	875	875	13.0	233	797	
225/75R17.5	16	133/130	M	HF111	M+S	TL	6.75	2725	2575	875	875	13.0	233	797	
225/75R17.5	16	143/141	J	HF628	M+S	TL	6.75	2725	2575	875	875	15.0	233	797	
245/70R17.5	16	136/134	M	FARS18	M+S	TL	7.5	2240	2120	850	850	13.0	248	789	
245/70R17.5	18	143/141 (140/140)	J/P	FARS18	M+S	TL	7.5	2725	2575	875	875	13.0	248	789	
245/70R19.5	16	135/133	M	HF111	TL	7.5	2180	2060	830	830	13.0	248	789		
245/70R19.5	16	136/134	M	FARS18	M+S	TL	7.5	2240	2120	825	825	14.0	248	789	
245/70R19.5	18	141/140	J	FARS18	M+S	TL	7.5	2575	2500	850	850	14.0	248	789	
255/70R22.5	16	140/137	L	HF660	-	TL	7.5	2500	2300	830	830	14.0	255	930	
255/70R22.5	16	140/137	L	HF111	-	TL	7.5	2500	2300	830	830	15.0	255	930	
265/70R19.5	16	140/138	M	FARS18	M+S	TL	7.5	2500	2360	775	775	14.0	262	867	
265/70R19.5	18	143/141	J	FARS18	M+S	TL	7.5	2725	2575	850	850	14.0	262	867	
265/70R19.5	16	140/144 (144/142)	L/M	FARS18	M+S	TL	8.25	3000	2800	850	850	14.0	283	895	
265/70R19.5	18	150/148	J	FARS18	M+S	TL	8.25	3350	3150	900	900	14.0	283	895	

Technical File

SIZE	PLY RATING	LOAD INDEX	SPEED RATING	PATTERN	M+S	TUBE	STANDARD R4	MAX LOAD (kg)		MAX PRESSURE (PSI)		THREAD DEPTH (mm)	SECTION WIDTH (mm)	OUTER DIAMETER (mm)
								SINGLE	DUAL	SINGLE	DUAL			
285/75R24.5	14	144/141	M	HF111	-	TL	8.25	2800	2575	760	760	15.5	283	1050
285/75R24.5	14	144/141	M	HF312	-	TL	8.25	2800	2575	760	760	22.0	283	1050
285/75R24.5	16	147/144	L	HF111	-	TL	8.25	3075	2800	830	830	15.5	283	1056
285/75R24.5	16	147/144	L	HF312	-	TL	8.25	3075	2800	830	830	22.0	283	1056
295/75R22.5	14	144/141	M	HF111	-	TL	9.00	2800	2575	760	760	15.5	298	1014
295/75R22.5	14	144/141	M	HF312	-	TL	9.00	2800	2575	760	760	20.0	298	1014
295/75R22.5	14	144/141	M	HF618	M+S	TL	9.00	2800	2575	760	760	11.0	298	1014
295/75R22.5	16	146/143	L	HF111	-	TL	9.00	3000	2725	830	830	15.5	298	1014
295/75R22.5	16	146/143	L	HF312	-	TL	9.00	3000	2725	830	830	20.0	298	1014
295/75R22.5	16	146/143	L	HF618	M+S	TL	9.00	3000	2725	830	830	11.0	298	1014
295/80R22.5	18	152/149	M	HF660	M+S	TL	9.00	3550	3250	900	900	15.0	298	1044
295/80R22.5	18	152/149	M	HF688	M+S	TL	9.00	3550	3250	900	900	15.0	298	1044
295/80R22.5	18	152/149	M	HF121	M+S	TL	9.00	3550	3250	900	900	16.5	298	1044
295/80R22.5	18	152/149	M	HF628	M+S	TL	9.00	3550	3250	900	900	20.5	298	1044
295/80R22.5	18	152/149	C	HF318	M+S	TL	9.00	3550	3250	900	900	21.5	298	1044
295/80R22.5	18	152/149	C	HF320	M+S	TL	9.00	3550	3250	900	900	21.5	298	1044
295/80R22.5	18	152/149	M	HF668	M+S	TL	9.00	3550	3250	900	900	18.0	298	1044
295/80R22.5	18	152/149	M	FARS15	M+S	TL	9.00	3550	3250	900	900	18.0	298	1044
295/80R22.5	18	152/149	K	FAMS17	M+S	TL	9.00	3550	3250	900	900	18.0	298	1044
315/70R22.5	20	154/150 (152/149)	L/M	HF660	M+S	TL	9.00	3750	3350	900	900	15.0	312	1014
315/70R22.5	20	154/150 (152/149)	L/M	HF121	M+S	TL	9.00	3550	3150	850	850	15.0	312	1014
315/70R22.5	20	154/152 (152/149)	L/M	HF638	M+S	TL	9.00	3750	3350	900	900	20.0	312	1014
315/70R22.5	20	154/150 (152/149)	L/M	HF628	M+S	TL	9.00	3750	3350	900	900	21.0	312	1014
315/80R22.5	20	156/152 (154/151)	L/M	HF660	M+S	TL	9.00	4000	3550	860	860	14.5	312	1076
315/80R22.5	20	156/152 (154/151)	L/M	HF606	M+S	TL	9.00	4000	3550	860	860	14.5	312	1076
315/80R22.5	20	156/152 (154/151)	L/M	HF121	M+S	TL	9.00	4000	3550	860	860	15.5	312	1076
315/80R22.5	20	156/152 (154/151)	L/M	HF122	M+S	TL	9.00	4000	3550	860	860	16.5	312	1076
315/80R22.5	20	156/152 (154/151)	L/M	HF124	M+S	TL	9.00	4000	3550	860	860	15.5	312	1076
315/80R22.5	20	156/152 (154/151)	L/M	ST011	M+S	TL	9.00	4000	3550	860	860	16.5	312	1076
315/80R22.5	20	156/152 (154/151)	L/M	HF768	M+S	TL	9.00	4000	3550	860	860	20.0	312	1076
315/80R22.5	20	156/152 (154/151)	L/M	HF638	M+S	TL	9.00	4000	3550	860	860	23.0	312	1076
315/80R22.5	20	156/152 (154/151)	L/M	HF628	M+S	TL	9.00	4000	3550	860	860	20.0	312	1076
315/80R22.5	20	156/152 (154/151)	L/M	HF322	M+S	TL	9.00	4000	3550	860	860	20.5	312	1076
315/80R22.5	20	156/152	K	FARS15	M+S	TL	9.00	4000	3550	860	860	16.5	312	1076
315/80R22.5	20	156/152	K	FAMS17	M+S	TL	9.00	4000	3550	860	860	17.0	312	1076
385/55R22.5	20	160/158	K/L	FTL311	M+S	TL	12.25	4500	4500	900	-	15.5	386	896
385/55R22.5	20	160	K	ST022	M+S	TL	11.75	4500	-	900	-	17.0	389	1072
385/55R22.5	20	160/158	K/L	FTL311	M+S	TL	11.75	4500	4500	900	-	16.0	389	1072
385/55R22.5	20	160/158	K/L	FTM313	M+S	TL	11.75	4500	4500	900	-	18.5	389	1072
425/65R22.5	20	165	K	FTL311	M+S	TL	13.00	5150	5150	825	-	16.0	430	1124
445/65R22.5	20	169	K	FTL311	M+S	TL	13.00	5800	5800	900	-	16.0	444	1150