



Tire Direct
La nueva generación

www.tiredirect.com.mx



TIRE DIRECT



/TIRE_DIRECT



/TIREDIRECTMX



TIRE DIRECT

NAVOLLA

NAVOLLA



SIZE

7.00R16

7.50R16

9.5R17.5 (SOON)

215/75R17.5 (SOON)

235/75R17.5 (SOON)

10.00R20

11.00R20

295/80R22.5 (SOON)

315/80R22.5

385/65R22.5

SIZE	PATTERN
11R22.5	    NV100 NV110 NV350U NV800
	    NV919 NV750 NV350 NV188
11.00R20	 NV101
315/80R22.5	    NV100 NV189 NV196 NV888
	  NV919 NV860

SIZE	PATTERN
385/65R22.5	   NV670 NV660 NV650
7.50R16LT	   NV100 NV777 NV999
7.00R16	   NV100 NV102 NV200

NV100



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
11R22.5	NV100	18PR	149/146L	1054	212	14.5	279	3250	3000	930	930
315/80R22.5	NV100	20PR	157/154K	1076	232	14.5	312	4125	3750	900	900
7.50R16LT	NV100	16PR	125/121L	802	160	12	210	1650	1450	870	870
7.00R16	NV100	14PR	118/114L	775	145	12	200	1320	1180	770	770

NV350U



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
11R22.5	NV350U	18PR	149/146L	1054	212	14.5	279	3250	3000	930	930

NV110



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
11R22.5	NV110	18PR	149/146L	1054	212	14.5	279	3250	3000	930	930

NV800



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
11R22.5	NV800	18PR	149/146L	1065	214	21.5	279	3250	3000	930	930

NV919



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
11R22.5	NV919	18PR	149/146L	1065	214	21.5	279	3250	3000	930	930
315/80R22.5	NV919	20PR	157/154K	1076	236	17	312	4125	3750	900	900

NV350



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
11R22.5	NV350	18PR	149/146L	1054	212	14.5	279	3250	3000	930	930

NV750



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
11R22.5	NV750	18PR	149/146L	1065	214	21	279	3250	3000	930	930

NV188



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
11R22.5	NV188	18PR	149/146L	1065	230	23	279	3250	3000	930	930

NV101



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
11.00R20	NV101	18PR	152/149L	1085	223	15.5	279	3550	3250	930	930

NV196



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
315/80R22.5	NV196	20PR	157/154K	1076	230	14	312	4125	3750	900	900

NV189



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
315/80R22.5	NV189	20PR	157/154K	1076	240	15	312	4125	3750	900	900

NV888



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
315/80R22.5	NV888	20PR	157/154K	1076	236	17	312	4125	3750	900	900

NV860



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
315/80R22.5	NV860	20PR	157/154K	1076	236	17	312	4125	3	750	900

NV660



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
385/65R22.5	NV660	20PR	160K	1072	277	14	389	4500	4500	900	900

NV670



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
385/65R22.5	NV670	20PR	160K	1072	277	14	389	4500	4	500	900

NV650



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
385/65R22.5	NV650	20PR	160K	1072	277	14	389	4500	4500	900	900

NV777



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
7.50R16LT	NV777	16PR	125/121L	802	154	12	210	1650	1450	870	870

NV102



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
7.00R16	NV102	14PR	118/114L	775	145	12	200	1320	1180	770	770

NV999



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
7.50R16LT	NV999	16PR	125/121L	802	170	13.5	210	1650	1450	870	870

NV200



SIZE	PATTERN	PR	LI/SS	O.D.(mm)	DRIVING SURFACE WIDTH	TREAD DEPTH	SIDEWALL SECTION (mm)	MAX LOAD (KG)		MAX PRESSUE (KPA)	
								SINGLE	DUAL	SINGLE	DUAL
7.00R16	NV200	14PR	118/114L	775	144	10.5	200	1320	1180	770	770