

NUMSIAM

PASSENGER CAR TIRE

Tire Direct 
La nueva generación



MADE IN THAILAND

NUMSIAM



Tire Direct 
La nueva generación

NUMSIAM



CATALOGUE |

目录 |

01 NMS688

02 NMS788

03 NMS855

04 NMS875

05 NMS895

06 NMS965

07 NMS985

08 NMS335

09 NMS337



- The features an aggressive asymmetric tread pattern engineered for optimal all-terrain performance.
- Its staggered shoulder blocks with stepped edges provide enhanced lateral grip on loose surfaces, while the deep, multi-pitch tread grooves ensure superior mud evacuation and hydroplaning resistance.
- The interlocking center tread design incorporates 3D siping technology for improved rock-crawling traction and stone ejection capabilities.
- The variable-pitch tread blocks reduce harmonic noise compared to conventional off-road patterns, maintaining highway comfort.

NMS600



Comfort



Low Noise



Drainage



Stability

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD 32NDS
LT235/75R15	6	104/101S	6 1/2J	28.86	9.25	14.5
31X10.50R15LT	6	109S	8 1/2J	30.52	10.54	14.5
245/70R16		111T XL	7J	29.53	9.76	12.2
265/70R16		112T	8J	30.63	10.71	12.2
265/75R16		116T	7 1/2J	31.65	10.51	12.2
LT225/75R16	10	115/112S	6J	29.29	8.78	15.1
LT235/85R16	10	120/116S	6 1/2J	31.73	9.25	15.1
LT245/75R16	10	120/116Q	7J	30.47	9.76	15.4
LT265/75R16	10	123/120Q	7 1/2J	31.65	10.51	15.4
LT285/75R16	10	126/123Q	8J	32.83	11.26	15.4
245/65R17		111T XL	7J	29.53	9.76	12.2
265/65R17		112T	8J	30.55	10.71	12.2
265/70R17		115S	8J	31.65	10.71	12.6
LT235/80R17	10	120/117S	6 1/2J	31.81	9.25	15.1
LT245/70R17	10	119/116S	7J	30.55	9.76	15.1
LT245/75R17	10	121/118S	7J	31.5	9.76	15.1
LT255/80R17	10	121/118R	7 J	33.07	10.04	15.1
LT265/65R17	10	120/117S	8J	30.55	10.71	15.1
LT265/70R17	10	121/118Q	8J	31.65	10.71	15.4
LT285/70R17	6	116/113Q	8 1/2J	32.76	11.5	15.4
LT285/70R17	10	121/118Q	8 1/2J	32.76	11.5	15.4
33X12.50R17LT	10	120R	10J	32.52	12.5	15.1
35X10.50R17LT	10	121R	8 1/2J	34.52	10.54	15.1

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD 32NDS
35X12.50R17 LT	10	121R	10J	34.52	12.5	15.1
35X12.50R17 LT	12	124R	10J	34.52	12.5	15.1
235/60R18		107H XL	7J	29.09	9.45	12.2
245/60R18		109H XL	7J	29.57	9.76	12.2
265/60R18		114T XL	8J	30.51	10.71	12.2
265/65R18		116T XL	8J	31.54	10.71	12.2
275/65R18		116T	8J	32.09	10.98	12.2
LT265/70R18	10	124/121S	8J	32.64	10.71	15.1
LT275/70R18	10	125/122S	8J	33.19	10.98	15.4
LT285/65R18	10	125/122R	8 1/2J	32.56	11.5	15.1
LT285/75R18	10	129/126R	8J	34.84	11.26	15.1
LT295/70R18	10	129/126R	8 1/2J	34.29	11.77	15.1
33X12.50R18LT	10	118R	10J	32.52	12.5	15.1
33X12.50R18LT	12	122R	10J	32.52	12.5	15.1
35X12.50R18LT	10	123R	10J	34.52	12.5	15.1
35X12.50R18LT	12	128R	10J	34.52	12.5	15.1
275/55R20		117T XL	8 1/2J	31.89	11.18	12.6
275/60R20		115T	8J	32.99	10.98	12.6
LT265/50R20	10	117/114S	8 1/2J	30.47	10.91	15.1
LT275/55R20	10	120/117S	8 1/2J	31.89	11.18	15.1
LT275/60R20	10	123/120R	8J	32.99	10.98	15.4
LT275/65R20	10	126/123S	8J	34.09	10.98	15.4
LT285/50R20	10	119/116S	9J	31.26	11.69	15.1
LT285/55R20	10	122/119S	9J	32.36	11.69	15.1



NMS600



Comfort



Low Noise



Drainage



Stability

- The features an aggressive asymmetric tread pattern engineered for optimal all-terrain performance.
- Its staggered shoulder blocks with stepped edges provide enhanced lateral grip on loose surfaces, while the deep, multi-pitch tread grooves ensure superior mud evacuation and hydroplaning resistance.
- The interlocking center tread design incorporates 3D siping technology for improved rock-crawling traction and stone ejection capabilities.
- The variable-pitch tread blocks reduce harmonic noise compared to conventional off-road patterns, maintaining highway comfort.

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD 32NDS
LT285/60R20	10	125/122R	8 1/2J	33.46	11.5	15.1
LT295/55R20	10	123/120R	9 1/2J	32.76	12.17	15.1
LT295/60R20	10	126/123R	8 1/2J	33.94	11.77	15.1
LT305/55R20	10	121/118Q	9 1/2J	33.23	12.44	15.1
LT305/55R20	12	125/122Q	9 1/2J	33.23	12.44	15.1
33X11.50R20LT	10	118Q	9J	32.52	11.42	15.1
33X12.50R20LT	10	114R	10J	32.52	12.5	15.1
33X12.50R20LT	10	114R	10J	32.52	12.5	15.1
33X12.50R20LT	12	119R	10J	32.52	12.5	15.1
35X12.50R20LT	10	121R	10J	34.52	12.5	15.1
35X12.50R20LT	10	121R	10J	34.52	12.5	15.1
35X12.50R20LT	12	125R	10J	34.52	12.5	15.1
37X13.50R20LT	10	127Q	11J	36.52	13.58	15.1
37X13.50R20LT	12	128Q	11J	36.52	13.58	15.1
285/45R22		114T XL	9 1/2J	32.09	11.22	12.2
305/40R22		114H XL	11J	31.61	12.32	12.2
305/45R22		118S XL	10J	32.8	11.93	12.5
LT285/50R22	10	121/118R	9J	33.27	11.69	15.1
33X12.50R22LT	10	109R	10J	32.52	12.45	15.1
33X12.50R22LT	10	109R	10J	32.52	12.45	15.1
33X12.50R22LT	12	114Q	10J	32.52	12.45	15.1
33X14.50R22LT	10	111Q	13J	32.52	14.46	15.1

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD 32NDS
35X12.50R22LT	10	117R	10J	34.52	12.5	15.1
35X12.50R22LT	12	121Q	10J	34.52	12.5	15.1
35X12.50R22LT	10	117R	10J	34.52	12.5	15.1
35X13.50R22LT	10	120Q	11J	34.52	13.58	15.1
35X15.50R22LT	12	123Q	13J	34.52	15.43	15.1
37X13.50R22LT	10	123Q	11J	36.52	13.58	15.1
37X13.50R22LT	12	128Q	11J	36.52	13.58	15.1
285/40R24		112H XL	10J	32.99	11.42	12.2
33X13.50R24LT	12	113Q	12J	32.52	13.78	15.1
33X14.50R24LT	12	118Q	13J	32.52	13.44	15.1
35X13.50R24LT	12	116Q	12J	34.52	13.44	15.1
35X15.50R24LT	10	118Q	13 1/2J	34.52	15.52	15.1
37X13.50R24LT	10	120Q	11J	36.52	13.58	15.1
37X13.50R24LT	12	124Q	11J	36.52	13.58	15.1
305/30R26		109H XL	11J	33.23	12.32	12.6
33X13.50R26LT	10	107Q	12 1/2J	32.52	13.58	15.1
33X14.50R26LT	10	108Q	13J	32.52	14.53	15.1
35X13.50R26LT	12	122Q	12J	34.52	13.58	15.1
35X15.50R26LT	12	120Q	14J	34.52	15.51	15.1
37X13.50R26LT	10	114Q	11J	36.52	13.44	15.1
37X13.50R26LT	12	117Q	11J	36.52	13.44	15.1
40X15.50R28LT	10	126P	13 1/2J	39.52	15.54	19.5



NMS700



Comfort



Low Noise



Drainage



Stability

• The patterns are engineered to balance aggressive off-road capability with on-road drivability, making them ideal for drivers who frequently tackle mixed terrains.
• Their tread patterns features are deep, staggered grooves and multi-pitch block designs to optimize traction on loose surfaces like gravel, mud, and rocks.
• The large reinforced shoulder blocks enhance sidewall protection and provide biting edges for climbing obstacles, while the wider tread voids prevent mud and debris buildup, maintaining grip in slippery conditions.
• This hybrid design as a versatile choice for adventurers seeking rugged performance without sacrificing highway manners.

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD 32NDS
LT235/80R17	10	120/117Q	6 1/2J	31.81	9.25	16
LT245/75R17	10	121/118Q	7J	31.5	9.76	16
LT265/70R17	10	121/118Q	8J	31.65	10.71	16
LT285/70R17	10	121/118Q	8 1/2J	32.76	11.5	16
33X12.50R17LT	10	120Q	10J	32.52	12.5	17.6
35X12.50R17LT	10	121Q	10J	34.52	12.5	17.6
40X13.50R17LT	8	121Q	11J	39.52	13.58	17.6
LT275/65R18	10	123/120Q	8J	32.09	10.98	16
LT275/70R18	12	128/125Q	8J	33.19	10.98	16
33X12.50R18LT	10	118Q	10J	32.52	12.5	17.6
35X12.50R18 LT	10	123Q	10J	34.52	12.5	17.6
275/55R20		117T XL	8 1/2J	31.89	11.18	13.2
285/55R20		116T XL	9J	32.36	11.69	13.2
305/55R20		116R XL	9 1/2J	33.23	12.44	13.2
LT265/60R20	10	121/118Q	8J	32.52	10.71	16
LT275/55R20	10	120/117Q	8 1/2J	31.89	11.18	16
LT275/65R20	12	128/125R	8J	34.09	10.98	16
LT285/55R20	10	122/119S	9J	32.36	11.69	16
LT285/65R20	10	127/124Q	8 1/2J	34.57	11.5	16
LT305/55R20	10	121/118S	9 1/2J	33.23	12.44	16
31X12.50R20LT	10	118Q	10J	30.51	12.52	16
31X13.50R20LT	10	121Q	11J	30.51	13.58	16
33X10.50R20LT	10	121Q	8 1/2J	32.52	10.54	17.6
33X11.50R20LT	10	118Q	9J	32.52	11.42	17.6
33X12.50R20LT	10	114Q	10J	32.52	12.5	17.6
33X12.50R20LT	10	114Q	10J	32.52	12.5	17.6
33X12.50R20LT	12	119Q	10J	32.52	12.5	17.6
33X14.50R20LT	12	120Q	11 1/2J	32.52	14.46	18.6
35X11.50R20LT	10	124Q	9J	34.52	11.42	16
35X12.50R20LT	10	121Q	10J	34.52	12.5	17.6
35X12.50R20LT	10	121Q	10J	34.52	12.5	17.6

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD 32NDS
LT235/80R17	10	120/117Q	6 1/2J	31.81	9.25	16
LT245/75R17	10	121/118Q	7J	31.5	9.76	16
LT265/70R17	10	121/118Q	8J	31.65	10.71	16
LT285/70R17	10	121/118Q	8 1/2J	32.76	11.5	16
33X12.50R17LT	10	120Q	10J	32.52	12.5	17.6
35X12.50R17LT	10	121Q	10J	34.52	12.5	17.6
40X13.50R17LT	8	121Q	11J	39.52	13.58	17.6
LT275/65R18	10	123/120Q	8J	32.09	10.98	16
LT275/70R18	12	128/125Q	8J	33.19	10.98	16
33X12.50R18LT	10	118Q	10J	32.52	12.5	17.6
35X12.50R18 LT	10	123Q	10J	34.52	12.5	17.6
275/55R20		117T XL	8 1/2J	31.89	11.18	13.2
285/55R20		116T XL	9J	32.36	11.69	13.2
305/55R20		116R XL	9 1/2J	33.23	12.44	13.2
LT265/60R20	10	121/118Q	8J	32.52	10.71	16
LT275/55R20	10	120/117Q	8 1/2J	31.89	11.18	16
LT275/65R20	12	128/125R	8J	34.09	10.98	16
LT285/55R20	10	122/119S	9J	32.36	11.69	16
LT285/65R20	10	127/124Q	8 1/2J	34.57	11.5	16
LT305/55R20	10	121/118S	9 1/2J	33.23	12.44	16
31X12.50R20LT	10	118Q	10J	30.51	12.52	16
31X13.50R20LT	10	121Q	11J	30.51	13.58	16
33X10.50R20LT	10	121Q	8 1/2J	32.52	10.54	17.6
33X11.50R20LT	10	118Q	9J	32.52	11.42	17.6
33X12.50R20LT	10	114Q	10J	32.52	12.5	17.6
33X12.50R20LT	10	114Q	10J	32.52	12.5	17.6
33X12.50R20LT	12	119Q	10J	32.52	12.5	17.6
33X14.50R20LT	12	120Q	11 1/2J	32.52	14.46	18.6
35X11.50R20LT	10	124Q	9J	34.52	11.42	16
35X12.50R20LT	10	121Q	10J	34.52	12.5	17.6
35X12.50R20LT	10	121Q	10J	34.52	12.5	17.6



- All-Terrain tires are engineered to balance on-road comfort and off-road capability, featuring tread patterns optimized for diverse conditions.
- The tread design typically includes aggressive, multi-pitched shoulder blocks to enhance grip on loose surfaces like gravel, mud, or sand, while maintaining stability during cornering.
- Larger, staggered tread blocks in the center provide robust traction and durability, reduce hydroplaning risk, and improve wet-weather performance.
- Additionally, reinforced sidewalls and siping on select tread blocks enhance puncture resistance and cold-weather grip.

NMS855



Comfort



Low Noise



Drainage




Stability

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD 32NDS
235/75R15XL		109T	6 1/2J	28.86	9.25	13.86
265/70R15 OWL		112T	8J	29.65	10.71	13.86
LT235/75R15	6	104/101R	6 1/2J	28.86	9.25	13.61
30X9.50R15LT	6	104S	7 1/2J	29.53	9.45	15.12
31X10.50R15LT	6	109R	8 1/2J	30.51	10.55	15.75
235/70R16		106T	7J	28.98	9.45	13.86
245/70R16XL		111T	7J	29.53	9.76	13.86
245/75R16		111T	7J	30.47	9.76	12.98
255/70R16		111S	7 1/2J	30.08	10.24	12.98
265/70R16		112T	8J	30.63	10.71	13.86
265/75R16		116T	7 1/2J	31.65	10.51	12.98
205R16LT	8	110/108T	6J	28.90	8.19	15.75
LT215/85R16	10	115/112Q	6J	30.39	8.50	13.61
LT225/75R16	10	115/112Q	6J	29.29	8.78	13.61
LT235/85R16	10	120/116Q	6 1/2J	31.73	9.25	15.75
LT245/75R16	10	120/116Q	7J	30.47	9.76	15.75
LT265/75R16	10	123/120R	7 1/2J	31.65	10.57	15.75
LT285/75R16	10	126/123R	8J	32.83	11.26	15.75
LT305/70R16	10	124/121R	9J	32.83	12.24	15.75
245/65R17XL		111T	7J	29.53	9.76	13.86
245/70R17		110S	7J	30.55	9.76	12.98
265/65R17		112T	8J	30.55	10.71	12.98
265/70R17		115T	8J	31.65	10.71	13.86

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD 32NDS
P285/70R17		117T	8 1/2J	32.76	11.50	12.98
LT235/80R17	10	120/117R	6 1/2J	31.81	9.25	13.61
LT245/70R17	10	119/116Q	7J	30.55	9.76	14.74
LT245/75R17	10	121/118R	7J	31.50	9.76	14.74
LT265/70R17	10	121/118R	8J	31.65	10.71	15.75
LT285/70R17	8	121/118S	8 1/2J	32.76	11.50	15.75
LT285/70R17	10	121/118S	8 1/2J	32.76	11.50	15.75
LT305/70R17	8	119/116R	9J	33.86	12.24	15.75
LT305/70R17	10	121/118S	9J	33.86	12.24	15.75
255/70R18		113S	7 1/2J	32.09	10.24	12.98
265/70R18		116T	8J	32.64	10.71	12.98
275/65R18		116T	8J	32.09	10.98	12.98
LT265/65R18	10	122/119Q	8J	31.54	10.71	14.74
LT265/70R18	10	124/121S	8J	32.64	10.71	14.74
LT275/65R18	10	123/120S	8J	32.09	10.98	14.74
LT275/70R18	10	125/122S	8J	33.19	10.98	14.74
LT305/60R18	10	121/118R	9J	32.40	12.24	15.75
275/55R20		113S	8 1/2J	31.89	11.18	10.96
275/60R20		115T	8J	32.99	10.98	10.96
LT265/60R20	10	121/118R	8J	32.52	10.71	14.74
LT275/55R20	10	120/117Q	8 1/2J	31.89	11.18	14.74
LT275/60R20	10	123/120Q	8J	32.99	10.98	14.74
LT275/65R20	10	126/123S	8J	34.09	10.98	14.74
LT285/55R20	10	122/119S	9J	32.36	11.69	15.75
LT285/65R20	10	127/124S	8 1/2J	34.57	11.50	15.75
LT305/55R20	10	121/118R	9 1/2J	33.23	12.44	15.75
35X12.50R20LT	10	121Q	10J	34.53	12.52	15.75



NMS075



- All-Terrain tires are engineered to balance on-road comfort and off-road capability, featuring tread patterns optimized for diverse conditions.
- The tread design typically includes aggressive, multi-pitched shoulder blocks to enhance grip on loose surfaces like gravel, mud, or sand, while maintaining stability during cornering.
- Larger, staggered tread blocks in the center provide robust traction and durability, reduce hydroplaning risk, and improve wet-weather performance.
- Additionally, reinforced sidewalls and siping on select tread blocks enhance puncture resistance and cold-weather grip.



NMS095



- All-Terrain tires are engineered to balance on-road comfort and off-road capability, featuring tread patterns optimized for diverse conditions.
- The tread design typically includes aggressive, multi-pitched shoulder blocks to enhance grip on loose surfaces like gravel, mud, or sand, while maintaining stability during cornering.
- Larger, staggered tread blocks in the center provide robust traction and durability, reduce hydroplaning risk, and improve wet-weather performance.
- Additionally, reinforced sidewalls and siping on select tread blocks enhance puncture resistance and cold-weather grip.

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD MM
P285/70R17		117T	8 1/2J	32.78	11.50	11
LT235/80R17	10	120/117R	6 1/2J	31.84	9.26	11.5
LT245/70R17	10	119/116Q	7J	30.57	9.77	12.1
LT245/75R17	10	121/118S	7J	31.52	9.77	12
LT265/70R17	10	121/118R	8J	31.68	10.72	12.5
LT285/70R17	8	121/118S	8 1/2J	32.78	11.50	12.5
LT305/70R17	8	119/116R	9J	33.88	12.25	12.5
235/60R18		107T	7J	29.12	9.46	8
255/55R18		109T	8J	29.04	10.44	8
265/60R18		110T	8J	30.54	10.72	9.2
265/70R18		116T	8J	32.66	10.72	11
275/65R18		116T	8J	32.11	10.99	11
285/60R18		116T	8 1/2J	31.48	11.50	11
LT265/70R18	10	124/121S	8J	32.66	10.72	12.5
LT275/65R18	10	123/120S	8J	32.11	10.99	12.5
LT275/70R18	10	125/122S	8J	33.21	10.99	12.5
P275/55R20		111S	8 1/2J	31.91	11.19	10.7
275/60R20		115T	8J	33.02	10.99	10.7
LT265/60R20	10	121/118R	8J	32.54	10.72	12.5
LT275/65R20	10	126/123S	8J	34.12	10.99	12.5
LT285/55R20	10	122/119S	9J	32.39	11.70	12.5
LT285/65R20	10	127/124S	8 1/2J	34.59	11.50	12.5
35X12.50R20LT	10	121Q	10J	34.55	12.53	12.5

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD MM
205/60R15		91H	6J	24.70	8.23	8.8
205/65R15		94H	6J	25.49	8.23	8.8
205/70R15		96T	6J	26.36	8.23	8.8
225/75R15		102S	6J	28.33	8.79	9.2
235/75R15XL		109T	6 1/2J	28.88	9.26	9.2
255/70R15		108T	7 1/2J	29.12	10.24	10.3
265/70R15		112T	8J	29.67	10.72	11
265/70R15 OWL		112S	8J	29.67	10.72	11
265/70R15 OWL		112Q	8J	29.67	10.72	11
31X10.50R15LT	6	109R	8 1/2J	30.54	10.56	12.5
31X10.50R15LT OWL	6	109Q	8 1/2J	30.54	10.56	12.5
LT215/75R15	6	100/97S	6J	27.70	8.51	10.8
LT215/75R15	6	100/97Q	6J	27.70	8.51	10.8
LT225/75R15	6	102/99S	6J	28.33	8.79	11.5
LT235/75R15	6	104/101R	6 1/2J	28.88	9.26	11.5
LT235/75R15	6	104/101Q	6 1/2J	28.88	9.26	11.5
LT235/75R15 OWL	6	104/101Q	6 1/2J	28.88	9.26	11.5
LT235/75R15	10	116/113S	6 1/2J	28.88	9.26	11.5
205/60R16		92H	6J	25.69	8.23	8.8



NMS965

- Mud-Terrain are engineered with aggressive, deep-tread patterns optimized for off-road performance in extreme conditions.
- Key tread features include large, widely spaced lugs that provide exceptional traction in mud, loose soil, and rocky terrain. The deep grooves and high void ratio allow the tread to self-clean by ejecting mud, sand, and debris, preventing clogging and maintaining grip.
- Multi-angled shoulder blocks enhance lateral stability and sidewall protection while biting into soft surfaces for added traction during climbs or sharp turns.



NMS895



- All-Terrain tires are engineered to balance on-road comfort and off-road capability, featuring tread patterns optimized for diverse conditions.
- The tread design typically includes aggressive, multi-pitched shoulder blocks to enhance grip on loose surfaces like gravel, mud, or sand, while maintaining stability during cornering.
- Larger, staggered tread blocks in the center provide robust traction and durability, reduce hydroplaning risk, and improve wet-weather performance.
- Additionally, reinforced sidewalls and siping on select tread blocks enhance puncture resistance and cold-weather grip.

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD 32NDS
LT305/65R17	10	121/118Q	9J	32.6	12.24	20.4
33X12.50R17LT	10	120Q	10J	32.52	12.5	20.4
LT305/60R18	10	121/118Q	9J	32.4	12.24	20.4
33X12.50R18LT	10	118Q	10J	32.52	12.5	20.4
LT275/55R20	10	120/117Q	8 1/2J	31.89	11.18	18.6
LT285/55R20	10	122/119Q	9J	32.36	11.69	18.6
33X11.50R20LT	10	118Q	9J	32.52	11.42	18.6
33X12.50R20LT	10	114Q	10J	32.52	12.5	20.4
33X12.50R20LT	10	114Q	10J	32.52	12.5	20.4
33X12.50R20LT	12	119Q	10J	32.52	12.5	20.4
33X13.50R20LT	12	120Q	11J	32.52	13.58	20.4
35X12.50R20LT	10	121Q	10J	34.52	12.5	20.4
35X12.50R20LT	10	121Q	10J	34.52	12.5	20.4
35X12.50R20LT	12	125Q	10J	34.52	12.5	20.4
35X13.50R20LT	12	126Q	11J	34.52	13.58	20.4
38X15.50R20LT	10	128Q	12 1/2J	37.52	15.54	20.4
40X15.50R20LT	12	128Q	12 1/2J	39.52	15.54	20.4
33X12.50R22LT	10	109Q	10J	32.52	12.45	20.4
33X12.50R22LT	10	109Q	10J	32.52	12.45	20.4
33X12.50R22LT	12	114Q	10J	32.52	12.45	20.4
33X13.50R22LT	12	116Q	11J	32.52	13.58	20.4
35X12.50R22LT	10	117Q	10J	34.52	12.5	20.4
35X12.50R22LT	10	117Q	10J	34.52	12.5	20.4
35X12.50R22LT	12	121Q	10J	34.52	12.5	20.4
35X13.50R22LT	12	122Q	11J	34.52	13.58	20.4
40X15.50R22LT	12	128Q	12 1/2J	39.52	15.54	20.4
33X13.50R24LT	10	109Q	12J	32.52	13.43	20.4
35X13.50R24LT	12	116Q	12J	34.52	13.44	20.4
38X15.50R24LT	12	128P	12 1/2J	37.52	15.43	20.4
40X15.50R24LT	12	128P	12 1/2J	39.52	15.54	20.4
35X13.50R26LT	10	118Q	12J	34.52	13.58	20.4
38X15.50R26LT	12	126P	13 1/2J	37.52	15.47	20.4
40X15.50R26LT	10	126P	12 1/2J	39.52	15.43	20.4
40X15.50R28LT	10	126P	13 1/2J	39.52	15.54	20.4
42X15.50R28LT	10	128P	13 1/2J	41.52	15.43	20.4

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD MM
215/65R16		98T	6 1/2J	27.03	8.71	8.2
215/70R16		100T	6 1/2J	27.90	8.71	9.2
225/70R16		103T	6 1/2J	28.45	8.98	9.2
225/70R16 XL		107T	6 1/2J	28.45	8.98	9.2
235/70R16		106T	7J	29.00	9.46	9.2
245/70R16 XL		111T	7J	29.55	9.77	10.3
245/75R16		111T	7J	30.50	9.77	10.3
255/70R16		111S	7 1/2J	30.10	10.24	10.3
265/70R16 OWL		112Q	8J	30.65	10.72	11
265/75R16 OWL		116T	7 1/2J	31.68	10.52	11
275/70R16 OWL		114S	8J	31.20	10.99	11
275/70R16 OWL		114Q	8J	31.20	10.99	11
205R16LT	8	110/108Q	6J	28.92	8.20	10.8
LT215/85R16	10	115/112Q	6J	30.42	8.51	10.8
LT225/75R16	10	115/112Q	6J	29.31	8.79	11.5
LT235/85R16	10	120/116S	6 1/2J	31.76	9.26	11.5
LT255/85R10	10	120/116Q	6 1/2J	31.76	9.26	11.5
LT245/75R16	10	120/116Q	7J	30.50	9.77	12.1
LT265/75R16	8	119/116Q	7 1/2J	31.68	10.52	12.5
LT265/75R16	10	123/120R	7 1/2J	31.68	10.52	12.5
LT285/75R16	10	126/123R	8J	32.86	11.27	12.5
LT305/70R16	10	124/121R	9J	32.86	12.25	12.5



NMS985



- Mud-Terrain are engineered with aggressive, deep-tread patterns optimized for off-road performance in extreme conditions.
- Key tread features include large, widely spaced lugs that provide exceptional traction in mud, loose soil, and rocky terrain. The deep grooves and high void ratio allow the tread to self-clean by ejecting mud, sand, and debris, preventing clogging and maintaining grip.
- Multi-angled shoulder blocks enhance lateral stability and sidewall protection while biting into soft surfaces for added traction during climbs or sharp turns.

NMS335



- Features an optimized tread pattern designed to balance fuel efficiency, all-season performance, and quiet comfort.
- Its tread design incorporates a combination of multi-directional grooves and rigid shoulder blocks, enhancing wet and dry traction by effectively channeling water away from the contact patch to reduce hydroplaning risks.
- The continuous center rib ensures stable handling and responsive steering, while the variable pitch tread blocks minimize road noise for a quieter ride.

TIRE SIZE	PLY RATING	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD MM
LT235/80R17	10	120/117Q	6 1/2J	31.84	9.26	13.5
LT255/75R17	6	111/108Q	7J	32.31	10.05	14.5
LT265/65R17	10	120/117Q	8J	30.81	10.72	14.2
LT265/70R17	10	121/118Q	8J	31.91	10.72	14.5
LT285/70R17	8	121/118Q	8 1/2J	33.02	11.50	14.5
LT285/70R17	10	121/118Q	8 1/2J	33.02	11.50	14.5
LT305/70R17	8	119/116Q	9J	34.12	12.25	14.5
35X12.50R17LT	10	121Q	10J	34.79	12.53	14.5
LT265/60R18	10	119/116Q	8J	30.77	10.72	14.2
LT275/70R18	10	125/122Q	8J	33.21	10.99	14.5
LT285/65R18	10	125/122Q	8 1/2J	32.82	11.50	14.5
33X12.50R18LT	10	118Q	10J	32.78	12.53	14.5
33X12.50R18LT	12	122Q	10J	32.78	12.53	14.5
35X12.50R18LT	10	123Q	10J	34.79	12.53	14.4
35X12.50R18LT	12	128Q	10J	34.79	12.53	14.4
LT275/65R20	10	126/123P	8J	34.36	10.99	14.5
LT285/55R20	10	122/119Q	9J	32.39	11.70	14.5
LT285/65R20	10	127/124Q	8 1/2J	34.83	11.50	14.5
LT305/55R20	10	121/118Q	9 1/2J	33.49	12.45	14.5
33X12.50R20LT	10	114Q	10J	32.78	12.53	15.8
33X12.50R20LT	12	119Q	10J	32.78	12.53	15.8
35X12.50R20LT	10	121Q	10J	34.79	12.53	15.8
35X12.50R20LT	12	125Q	10J	34.79	12.53	15.8
37X13.50R20LT	10	127Q	11J	36.80	13.59	15.7
37X13.50R20LT	12	128Q	10J	36.80	12.53	15.7
38X15.50R20LT	8	125Q	12J	37.78	15.56	15.7
33X12.50R22LT	10	109Q	10J	32.54	12.53	15.8
33X12.50R22LT	12	114Q	10J	32.54	12.53	15.8
35X12.50R22LT	10	117Q	10J	34.55	12.53	15.8
35X12.50R22LT	12	121Q	10J	34.55	12.53	15.8
37X13.50R22LT	10	123Q	11J	36.80	13.59	15.7
37X13.50R22LT	12	128Q	11J	36.80	13.59	15.7
35X12.50R24LT	10	117Q	10 1/2J	34.79	12.45	15.7
37X13.50R24LT	10	120Q	11J	36.80	13.59	15.7

TIRE SIZE	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD MM
145/70R12	69T	4.50B	20.05	5.91	7.1
155/70R12	73T	4.50B	20.61	6.19	7.1
165/70R12	77T	5.00B	21.16	6.70	6.8
155/65R13	73T	4 1/2J	20.96	6.19	7.6
155/70R13	75T	4 1/2J	21.59	6.19	7.6
155/80R13	79T	4 1/2J	22.77	6.19	7.6
155/80R13	83XL S	4 1/2J	22.77	6.19	7.6
165/65R13	77T	5J	21.43	6.70	7
165/70R13	79T	5J	22.14	6.70	6.8
165/80R13	83T	4 1/2J	23.40	6.50	7.3
175/60R13	77H	5.00B	21.28	6.97	7
175/70R13	82T	5J	22.69	6.97	7
185/70R13	86T	5 1/2J	23.25	7.45	7.6
155/65R14	75H	4 1/2J	21.99	6.19	7.1
165/60R14	75H	5J	21.83	6.70	6.8
165/65R14	79H	5.00B	22.46	6.70	6.8
165/70R14	81H	5J	23.17	6.70	6.8
165/70R14	85XL T	5J	23.17	6.70	6.8
175/60R14	79H	5J	22.30	6.97	6.8
175/65R14	82H	5J	23.01	6.97	7
175/65R14	86XL T	5J	23.01	6.97	7
175/70R14	84H	5J	23.72	6.97	7
175/70R14	88XL T	5J	23.72	6.97	7
185/60R14	82H	5 1/2J	22.77	7.45	7.3
185/65R14	86H	5 1/2J	23.48	7.45	7.3
185/70R14	88H	5 1/2J	24.27	7.45	7.3
195/60R14	86H	6J	23.25	7.92	7.3



NMS335



NMS337



- Features an optimized tread pattern designed to balance fuel efficiency, all-season performance, and quiet comfort.
- Its tread design incorporates a combination of multi-directional grooves and rigid shoulder blocks, enhancing wet and dry traction by effectively channeling water away from the contact patch to reduce hydroplaning risks.
- The continuous center rib ensures stable handling and responsive steering, while the variable pitch tread blocks minimize road noise for a quieter ride.

TIRE SIZE	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD MM
195/70R14	91H	6J	24.82	7.92	7.6
205/60R14	88H	6J	23.72	8.23	7.8
205/70R14	95H	6J	25.37	8.23	7.8
215/70R14	96H	6 1/2J	25.93	8.71	7.8
175/55R15	77H	5 1/2J	22.58	7.17	7
175/60R15	81H	5J	23.29	6.97	7
175/65R15	84H	5J	23.99	6.97	7.1
185/55R15	82H	6J	23.05	7.64	7
185/55R15	82V	6J	23.05	7.64	7
185/60R15	84H	5 1/2J	23.76	7.45	7.3
185/60R15	88XL H	5 1/2J	23.76	7.45	7.3
185/65R15	88H	5 1/2J	24.47	7.45	7.3
185/65R15	92XL T	5 1/2J	24.47	7.45	7.3
195/60R15	88H	6J	24.23	7.92	7.3
195/60R15	88V	6J	24.23	7.92	7.3
195/65R15	91H	6J	25.02	7.92	7.3
195/65R15	91V	6J	25.02	7.92	7.3
195/65R15	95XL H	6J	25.02	7.92	7.3
205/60R15	91V	6J	24.70	8.23	7.8
205/60R15	91H	6J	24.70	8.23	7.8
205/65R15	94H	6J	25.49	8.23	7.6
205/65R15	94V	6J	25.49	8.23	7.6
205/70R15	96H	6J	26.36	8.23	7.8
215/60R15	94H	6 1/2J	25.18	8.71	7.8
215/65R15	96H	6 1/2J	26.04	8.71	7.8
215/70R15	98H	6 1/2J	26.91	8.71	7.8
225/70R15	100H	6 1/2J	27.46	8.98	7.8
205/55R16	91V	6 1/2J	24.90	8.43	7.6
205/60R16	92V	6J	25.69	8.23	7.8
205/60R16	92H	6J	25.69	8.23	7.8

TIRE SIZE	LOAD/SPEED INDEX	STANDARD RIM	OD INCH	SW INCH	TD 32NDS
195/75R14	92S	5.5	25.51	7.72	10.5
205/75R14	95S	5.5	26.14	7.99	10.5
215/75R14	98S	6	26.69	8.50	10.5
205/70R14	93S	6	25.35	8.23	10.5
215/70R14	96S	6.5	25.91	8.70	10.5
205/75R15	97S	5.5	27.13	7.99	10.5
215/75R15	100S	6	27.68	8.50	10.5
225/75R15	102S	6	28.31	8.78	10.5
235/75R15	105S	6.5	28.86	9.25	10.5
205/70R15	95S	6	26.34	8.23	10.5
215/70R15	97S	6.5	26.89	8.70	10.5
225/70R15	100S	6.5	27.44	8.98	10.5