

TAITONG

Tire Direct
La nueva generación



TBR TIRE
All Steel Heavy Radial Tyre Series

Tire Direct
La nueva generación



Bld. Campestre No. 72
Col. Casa Blanca, León, Gto.
C.P. 37170



+52 (477) 718.09.21
01800 000TIRE (8473)



info@tiredirect.com.mx
www.tiredirect.com.mx



Tire Direct



Tire Direct



QUALIFICATION CERTIFICATE

SASO	ECE R117	SONCAP	DOT	
INMETRO	TS16949	SMARTWAY	GCC	ECE R54



LONG HAUL & REGIONAL

ON-OFF ROAD

OFF ROAD

ROAD



POSITION



ALL POSITION



STEER



DRIVE




TRAILER





Pattern characteristic:
Specially recipe design provides tear resistance, high wear resistance, and excellent load capacity, Low rolling resistance & noise emission, excellent heat radiation, guiding stability. Excellent fuel efficiency.
Suitable conditions:
Suitable for steer/trailer position of bus and truck running on high-grade road.

HS101



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11R22.5	16	8.25	146/143M	1050	279	3000/2725	830
12R22.5	18	9.00	152/149M	1084	300	3550/3250	930
295/80R22.5	18	9.00	152/149M	1044	298	3550/3250	900
315/80R22.5	20	9.00	157/153L	1076	312	4125/3650	860



Pattern characteristic:
Low heat generating, excellent high speed driving character, good handling quality.
Suitable conditions:
Suitable for steer/trailer position. Steer and trailer wheel, suitable for high way and good quality road use.

HS109



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
315/80R22.5	20	9.00	157/153L	1076	312	4125/3650	860



Pattern characteristic:
Suitable for medium/long-haul vehicles Running on high-grade road, excellent load capacity, straight shallow grooves offers an excellent drive, straight ride and anti-sidewall scuffing performance.
Suitable conditions:
Suitable for steer/trailer position, Running on the nation highway and high way.

HS201



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
315/70R22.5	20	9.00	154/150M	1014	312	3750/3350	900



Pattern characteristic:
Improved tread design, High wear resistance and eccentric wear resistance. Low rolling resistance, Save fuel consumption, good handling quality.
Suitable conditions:
Steer/trailer tyre suitable for Long-distance transportation, running on high-grade road.

HS205



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11R22.5	16	8.25	146/143M	1050	279	3000/2725	830
11R24.5	16	8.25	149/146L	1100	279	3250/3000	830
205/75R17.5	14	6.00	124/122M	753	205	1600/1500	750
215/75R17.5	16	6.00	126/124M	767	212	1700/1600	700
225/70R19.5	14	6.75	128/126M	811	226	1800/1700	760
235/75R17.5	16	6.75	132/130M	797	233	2000/1900	775
245/70R19.5	16	7.50	135/133M	833	248	2180/2060	830
255/70R22.5	16	7.50	140/137M	930	255	2500/2300	830
265/70R19.5	16	7.50	140/138M	867	262	2500/2360	775
275/70R22.5	16	8.25	148/145M	958	276	3150/2900	900
285/75R24.5	16	8.25	147/144L	1056	283	3075/2800	830
295/75R22.5	16	9.00	146/143L	1014	298	3000/2725	830



Pattern characteristic:
High wear resistance, High cost performance. Excellent anti-side-skid character and good drainage character, good handling quality.
Suitable conditions:
Suitable for steer/trailer position of buses and light trucks running on Highway.

HS219



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11R22.5	14	8.25	144/142M	1050	279	2800/2650	720
11R24.5	14	8.25	146/143M	1100	279	3000/2725	720
285/75R24.5	14	8.25	144/141L	1056	283	2800/2575	760
295/75R22.5	14	9.00	144/141L	1014	298	2800/2575	760




Pattern characteristic:
Mixed pattern design provide strong traction and breaking power. Longer block pattern design enhance the ability of anti eccentric wear and the abnormal wear. Five deep grooves, multi blocks & tiny kerfs.
Suitable conditions:
Suitable for driving wheel position, no suitable for steer position of short/middle distance trucks running on good road condition.



HS258

Pattern characteristic:
Four straight groove can provide excellent braking and driving performances.
Suitable conditions:
Suitable for steering wheel, trailer wheel, medium/long-haul vehicles, Running on good pavements.



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930



HS102



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
315/80R22.5	20	9.00	157/153L	1076	312	4125/3650	860

Pattern characteristic:
TMS technology and special compound for smooth tread wear. Special pattern design provides good anti eccentric wear. Block tread.
Suitable conditions:
Suitable for driving wheel position of middle/long distance trucks running on good road condition.



HS259

Pattern characteristic:
4 straight groove can provide superior braking and driving performances, superior adhesion properties of the ground, excellent wet skid resistance, eccentric wear resistance.
Suitable conditions:
steer and trailer tyre, medium/long-haul vehicles, running on high-grade road.



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930



HS103



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11R22.5	16	8.25	146/143M	1050	279	3000/2725	830
12R22.5	18	9.00	152/149M	1084	300	3550/3250	930
295/80R22.5	18	9.00	152/149M	1044	298	3550/3250	900

Pattern characteristic:
Specially recipe design provides wear-resistance, low heat generation, Excellent traction and draining performance, more original mileage. Mix pattern supplies excellent traction performance, braking performance, supper driving and anti-wet ability.
Suitable conditions:
Suitable for driving position, medium/long-haul vehicles, running on high-grade road.



HS303

Pattern characteristic:
Four straight groove can provide excellent braking and driving performances.
Suitable conditions:
Suitable for steering wheel, trailer wheel, medium/long-haul vehicles, Running on good pavements.



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
295/80R22.5	18	9.00	152/149M	1044	298	3550/3250	900



HS107



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
12R22.5	18	9.00	152/149M	1084	300	3550/3250	930
13R22.5	18	9.75	154/151L	1124	320	3750/3450	850



Pattern characteristic:
Mixed pattern design provide strong traction and breaking power . Longer block pattern design enhance the ability of anti eccentric wear and the abnormal wear. Five deep grooves, multi blocks & tiny kerfs on the blocks assure a firm grip and a powerful tr
Suitable conditions:
Suitable for driving wheel position on good road condition.

HS202



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
295/80R22.5	18	9.00	152/149M	1044	298	3550/3250	900
315/70R22.5	20	9.00	154/150M	1014	312	3750/3350	900



Pattern characteristic:
Suitable for highway and good quality road condition drive wheel, trailer wheel suitable for common or poor road surface, such as country road with anti-crack character, good abrasion resistance, anti-puncture character, excellent traction performance and loading character deepened & widened pattern of groove design, increase the traveled range and improve the adaptability to bad roads steering wheel , trailer wheel.
Suitable conditions:
Suitable for driving position of buses and light trucks running on Highway and roads of common grades.

HS207



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11R22.5	16	8.25	146/143M	1050	279	3000/2725	830
11R24.5	16	8.25	149/146L	1100	279	3250/3000	830



Pattern characteristic:
Widen tread width design provides excellent driving and gripping power. Extra deep tread provides an extra powerful traction and a long tread life. Closed shoulder maintains a good irregular wear resistance. With excellent crack and tear resistance character.
Suitable conditions:
Suitable for Light, heavy duty and bus driving position on good road.

HS208



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11R22.5	16	8.25	146/143M	1050	279	3000/2725	830
11R24.5	16	8.25	149/146L	1100	279	3250/3000	830
285/75R24.5	16	8.25	147/144L	1056	283	3075/2800	830
295/75R22.5	16	9.00	146/143L	1014	298	3000/2725	830



Pattern characteristic:
Excellent load capacity and Super abrasion resistance, tear resistance, high wear resistance, suitable to vehicles on low grade road and medium/long-haul vehicles.
Suitable conditions:
Drive position. High-grade road.

HS716



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930
12R22.5	18	9.00	152/149K	1084	300	3550/3250	930



Pattern characteristic:
High wear resistance, High cost performance.
Suitable conditions:
Suitable for trailer position of buses and light trucks running on Highway.

HS206



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
7.50R16LT	14	6.00G	122/118L	802	210	1500/1320	770
9.5R17.5	18	6.75	143/141M	842	240	2725/2575	930



EU
Pattern characteristic:
Excellent traction and draining performance, more original mileage.
Suitable conditions:
trailer tyre of bus and truck, not suitable for drive and steer wheel position running on well-paved roads and mixed pavements and medium/long-haul vehicles.

HS106



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
385/65R22.5	20	11.75	160K	1072	389	4500	900



HS166

Pattern characteristic:
Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage, Excellent fuel efficiency.
Suitable conditions:
Suitable for all wheel position, medium/long-haul vehicles, running on mixed pavements.



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
385/65R22.5	20	11.75	160K	1072	389	4500	900



HS18

Pattern characteristic:
Reinforced belt and body construction enhance the loading ability. Special tread compound for high resistance against tread cut.
Suitable conditions:
Suitable for all position on good road condition and non-paved roads.



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
12.00R24	20	8.50	160/157K	1226	313	4500/4125	900



HS209

Pattern characteristic:
Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage, Excellent fuel efficiency.
Suitable conditions:
Suitable for all wheel position, medium/long-haul vehicles, running on mixed pavements.



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
385/65R22.5	20	11.75	160K	1072	389	4500	900



Pattern characteristic:
3 continuous ribs, and the circumferential grooves enhance superior adhesion properties of the ground, excellent wet skid resistance, special tread design, providing a low heating up, wear resistance.
Suitable conditions:
Suitable for all wheel position, running on high way, running on mixed pavements, the national highway.

HS216



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
12.00R24	20	8.50	160/157K	1226	313	4500/4125	900



Pattern characteristic:
Block tread pattern provides excellent gripping and traction power. Tough belt construction for smooth wear and longer mileage. Special tread compound for high resistance against tread cut.
Suitable conditions:
Suitable for all position of trucks running on non-paved roads.

HS218K



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
12.00R24	20	8.50	160/157K	1226	313	4500/4125	900



Pattern characteristic:
Block tread pattern provides excellent gripping and traction power. Tough belt construction for smooth wear and longer mileage. Special tread compound for high resistance against tread cut.
Suitable conditions:
Suitable for all position of trucks running on non-paved roads.

HS218



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
10.00R20	18	7.50	149/146K	1052	275	3250/3000	930
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930
12.00R20	20	8.50	156/153K	1122	313	4000/3650	900
9.00R20	16	7.00	144/142K	1018	258	2800/2650	900



Pattern characteristic:
Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage, excellent fuel efficiency.
Suitable conditions:
Suitable for all wheel position, medium/long-haul vehicles, running on mixed pavements.

HS268



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
10.00R20	18	7.50	149/146K	1052	275	3250/3000	930
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930
11R22.5	16	8.25	146/143M	1050	279	3000/2725	830
12.00R20	20	8.50	156/153K	1122	313	4000/3650	900
12.00R24	20	8.50	160/157K	1226	313	4500/4125	900
12R22.5	18	9.00	152/149M	1084	300	3550/3250	930
13R22.5	18	9.75	154/151L	1124	320	3750/3450	850
315/80R22.5	20	9.00	157/153L	1076	312	4125/3650	860
6.50R16LT	12	4.50	110/105K	755	182	1060/925	670
7.00R16LT	14	5.50F	118/114K	778	202	1500/1320	770
7.50R16LT	14	6.00G	122/118L	802	210	1500/1320	770
8.25R16LT	16	6.50H	128/124K	860	230	1800/1600	770
8.25R20	16	6.50	139/137K	974	236	2430/2300	930
9.00R20	16	7.00	144/142K	1018	258	2800/2650	900



Pattern characteristic:
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.
Suitable conditions:
Suitable for all wheel position with short mileage vehicles running on various of non-paved roads.

HS958+



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930
12.00R20	20	8.50	156/153K	1122	313	4000/3650	900



Pattern characteristic:
Reinforced belt and body construction enhance the loading ability. Special tread compound for high resistance against tread cut.
Suitable conditions:
Suitable for driving wheel position on good road condition and non-paved roads.

HS108



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
12.00R24	20	8.50	160/157K	1226	313	4500/4125	900



Pattern characteristic:
Reinforced belt and body construction enhance the loading ability. Special tread compound for high resistance against tread cut.
Suitable conditions:
Suitable for driving wheel position on good road condition and non-paved roads.

HS217



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11R22.5	16	8.25	146/143M	1050	279	3000/2725	830
11R24.5	16	8.25	149/146L	1100	279	3250/3000	830



Pattern characteristic:
Reinforced belt and body construction enhance the loading ability. Special tread compound for high resistance against tread cut.
Suitable conditions:
Suitable for driving wheel position on good road condition and non-paved roads.

HS228



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
12.00R24	20	8.50	160/157K	1226	313	4500/4125	900



Pattern characteristic:
Tire adopt super structure, with excellent carrying capacity, super wear-resistant and anti-puncture tread formulation, suitable for poor road condition, dedicated to the short-distance use.
Suitable conditions:
Driving position, Ordinary Road, bad road.

HS718



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
12.00R20	20	8.50	156/153K	1122	313	4000/3650	900



Pattern characteristic:
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.
Suitable conditions:
Suitable for driving wheel position on good road condition and non-paved roads.

H5918



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930
12.00R20	20	8.50	156/153K	1122	313	4000/3650	900
12.00R24	20	8.50	160/157K	1226	313	4500/4125	900
7.50R16LT	14	6.00G	122/118L	802	210	1500/1320	770
8.25R16LT	16	6.50H	128/124K	860	230	1800/1600	770



Pattern characteristic:
Tough belt construction, with high wear resistance and good impact force, Reinforced bead provide good traction.
Suitable conditions:
Suitable for driving wheel position of short/middle distance trucks on various of non-paved road.

H5918+



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
10.00R20	18	7.50	149/146K	1052	275	3250/3000	930



Pattern characteristic:
Block tread pattern provides excellent gripping and traction power. Tough belt construction for smooth wear and longer mileage. Special tread compound for high resistance against tread cut.
Suitable conditions:
Suitable for driving position of trucks running on non-paved roads.

H5928



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
315/80R22.5	20	9.00	157/153L	1076	312	4125/3650	860
9.5R17.5	18	6.75	143/141M	842	240	2725/2575	930



Pattern characteristic:
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.
Suitable conditions:
Suitable for driving wheel position for short mileage vehicles running on various of non-paved roads.

H5938+



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930
12.00R20	20	8.50	156/153K	1122	313	4000/3650	900



Pattern characteristic:
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.
Suitable conditions:
Suitable for driving wheel position for short mileage vehicles running on various of non-paved roads.

H5968+



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930
12.00R20	20	8.50	156/153K	1122	313	4000/3650	900



Pattern characteristic:
Big deep block provide strong traction and braking power. Open groove and bottom design given excellent self-cleaning performance Reinforced bead and body to strengthen the puncture resistance, tear resistance.
Suitable conditions:
Suitable for driving wheel position for short mileage vehicles running on various of non-paved roads.

H5978



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
10.00R20	18	7.50	149/146K	1052	275	3250/3000	930



Pattern characteristic:
Super abrasion resistance, excellent heat dissipation performance, good handling and traction, with higher original mileage, Excellent fuel efficiency.
Suitable conditions:
Suitable for drive wheel position, use for mining/mountain road, medium/long-haul vehicles, running on mixed pavements.

HS203



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
315/80R22.5	20	9.00	157/153L	1076	312	4125/3650	860



Pattern characteristic:
Transverse big block type and deepened pattern design, provides superior driving performance. The open type groove design has a good self-cleaning ability. In particular, the strength of reinforced carcass design, provide greater carrying capacity. In par.
Suitable conditions:
Overload, bad road short haul dump truck driving wheel or all wheel position. The construction site, mines, mud and other serious adverse road conditions.

HS715



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
10.00R20	18	7.50	149/146K	1052	275	3250/3000	930
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930
12.00R20	20	8.50	156/153K	1122	313	4000/3650	900
9.00R20	16	7.00	144/142K	1018	258	2800/2650	900



Pattern characteristic:
Special designed mine pattern tyre for harsh road, with wide tyre crown and deep tread, which could provide higher mileage. The large lateral pattern block can produce the driving forces, maintaining excellent grip performance both in the dry and wet pavement.
Suitable conditions:
Truck drive tyre, use for Mining/Mountain road.

HS725



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930
12.00R20	20	8.50	156/153K	1122	313	4000/3650	900



Pattern characteristic:
Transverse big block type and deepened pattern design, provides superior driving performance. The open type groove design has a good self-cleaning ability. In particular, the strength of reinforced carcass design, provide greater carrying capacity. In par.
Suitable conditions:
Overload, bad road short haul dump truck driving wheel or all wheel position. The construction site, mines, mud and other serious adverse road conditions.

HS735+



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930
12.00R20	20	8.50	156/153K	1122	313	4000/3650	900



Pattern characteristic:
Special designed mine pattern tyre for harsh road, with wide tyre crown and deep tread, which could provide higher mileage. The large lateral pattern block can produce the driving forces, maintaining excellent grip performance both in the dry and wet pavement.
Suitable conditions:
Truck drive tyre, use for Mining/Mountain road.

HS755+



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930
12.00R20	20	8.50	156/153K	1122	313	4000/3650	900



Pattern characteristic:
Unique belt structure, with high wear-resistance and low producing heat crown formulation. Has a strong grip and wet-slip resistance performance. Optimized and enhanced bead design, especially for special conditions. Radial structure of the carcass, ma.
Suitable conditions:
Truck drive tyre, suitable for low speed ride on bad or common road, such as mine road, mountain road.

HS801Q



SIZE	PR	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
10.00R20	18	7.50	149/146K	1052	275	3250/3000	930
11.00R20	18	8.00	152/149K	1082	286	3550/3250	930
12.00R20	20	8.50	156/153K	1122	313	4000/3650	900
13R22.5	18	9.75	154/151L	1124	320	3750/3450	850



5.50-13 6.00-13 6.50-14 6.00-15 6.00-16 6.50-15 7.00-15 7.00-16 7.50-15 7.50-16
7.50-20 8.25-16 8.25-20 9.00-20 10.00-20 11.00-20 12.00-20

The tyres have small in rolling resistance and sideslip-preventing.They are suitable for driving in high speed and saving oil and beneficial.

HS228



5.00-16 5.50-16 6.50-15 6.50-14 6.50-16 7.00-16 7.50-16 7.50-20 8.25-16
8.25-20 9.00-16 9.00-20 10.00-20 11.00-20 12.00-20

The tyres are suitable for driving on sandstone road with good standing wear and high in loading ability.

HS868



14.00-24 17.5-25 20.5-25 23.5-25 16.00-25 26.5-25 16/70-20 13.00-25 18.00-25 29.5-25
16/70-24

For the complex,variable and harsh conditions of use,the tyres have the different featurres of wearing resistance and wearing cutted,safe and reliable.

HS668

Tyre Size	Ply Rating	Rim		Inflated Dimensions		Max Load		Inflation Pressure
		Standard Rim	Permitted Rim	Section Width (mm)	Overall Diameter (mm)	Sinle Load	Dual Load	
5.00-16LT	8	3.50	3 1/2J 4.00B	145	685	375	-	250
5.50-16LT	8	4.00	4 1/2J	165	705	425	-	250
550-13LT	6.8	4J	4 1/2J 5J	160	620	565	500	420
6.00-14LT	6.8		4J5J	170	680	685	600	420
6.00-15LT	6.8	4.50E	4 1/2K	170	705	720	630	420
6.00-16LT	6.8.10	4.50E	4.00E	170	730	860	755	530
7.50-20	8.10.12.14	6.0	6.00T 6.5 6.50T	215	935	1885	1655	810
*7.50-16LT	6.8.10.12.14	5.50F	6.00G	200	775	1220	1075	630
*11.00-20	12.14.16.18	8.0	8.00V 8.5 8.5V5 ⁸ 8.50V	293	1085	3270	2870	810
12.00-20	16.18	8.5	8.50V 8.50V5 ⁹ 9.00V	315	1125	3730	3270	810
6.00-13LT	6.8		4J5J	170	655	655	570	6.8.
6.00-14LT	6.8		4J5J	170	680	685	600	420
6.00-15LT	6.8	4.50E	4 1/2K	170	705	720	630	420
6.00-16LT	6.8.10	4.50E	4.00E	170	730	860	755	530
6.50-14LT	6.8	4 1/2J	5J	180	705	785	690	420
6.50-15LT	6.8	4.50E	4 1/2K 5K 5 1/2K 5.50F	180	730	820	720	420
*6.50-16LT	6.8.10.12	5.50F	5.00E 5.50F	185	750	975	860	530
7.00-15LT	6.8.10	5.50F	6.00G	200	750	1040	915	530
*7.00-16LT	6.8.10.12.14	5.50F	6.00G	200	775	1220	1075	630
7.50-15LT	8.10.12	6.00G	5.50F 6.50H	215	780	1370	1210	630
*7.50-16LT	6.8.10.12.14	6.00G	5.50F 6.50H	215	805	1405	1240	630
*8.25-16LT	6.8.10.12.14.16	6.50H	6.00G	235	855	1705	1500	630
9.00-16LT	6.8.10.12.14	6.50H	6.00G 7.00H	255	890	1955	1720	630

Tyre Size	Ply Rating	Rim		Inflated Dimensions		Max Load		Inflation Pressure
		Standard Rim	Permitted Rim	Section Width (mm)	Overall Diameter (mm)	Sinle Load	Dual Load	
7.50-20	8.10.12.14	6.0	6.00T 6.5 6.50T	215	935	1885	1655	810
8.25-20	10.12.14.16	6.5	6.50T 7.0 7.00T 7.0T50	235	974	2205	1940	810
9.00-20	10.12.14.16	7.0	7.00T 7.0T50 7.5 6.5 7.50V	259	1018	2575	2255	770
10.00-20	12.14.16.18	7.5	7.50V 8.0 8.00V 8.0V50	278	1055	3000	2630	810
11.00-20	12.14.16.18	8.0	8.00V 8.5 8.5V50 8.50V	293	1085	3270	2870	810
12.00-20	16.18	8.5	8.50V 8.50V50 9.00V	315	1125	3730	3270	810
10.00-20	12.14.16.18	7.5	7.50V 8.0 8.00V 8.0V50	278	1055	3000	2630	810
11.00-20	12.14.16.18	8.0	8.00V 8.5 8.5V50 8.50V	293	1085	3270	2870	810
12.00-20	16.18	8.5	8.50V 8.50V50 9.00V	315	1125	3730	3270	810



23.5-25

The tyres have the features of good grasping force to ground,standing the sideslip-preventing,and the tyres are suitable for all kinds of conditions of road and climates.

HS866



23.5-25

With strong ground grip, good self-cleaning, good standing wear and high in loading ability.

HS686



6.00-13 6.00-14 6.00-15 6.50-16 7.00-16 7.50-16 8.25-16 9.00-20 10.00-20 11.00-20

With strong ground grip, good self-cleaning, good standing wear and high in loading ability.

HS118

Tyre Size	Ply Rating	Rim		Inflated Dimensions		Max Load			Inflation Pressure	Valve Size
		Standard Rim	Permitted Rim	Section Width (mm)	Overall Diameter (mm)	65 km/h	50 km/h	15 km/h		
17.5-25	18	14.00/1.5	—	445	1398	-	-	5440	280	Z1-01-8
20.5-25	20	17.00/20	—	520	1548	4880	5900	6580	350	Z1-01-6
23.5-25	20	19.5/2.5	—	595	1673	5530	6680	7460	280	Z1-01-8
14.00-24	16/24	10.00	—	375	1370	4760/6030			420/630	Z1-01-8
16.00-25	20/28	11.25/2.0	—	430	1546	6220/7360			420/560	Z1-01-8
26.5-25	16/20	22.00/3.0	—	675	1750	11500/13200			275/350	Z1-01-8
16/70-20	10/14	13.00	—	410	1075	4200/5150			325/450	Z1-01-8
18.00-25	20/28	13.00/2.5	—	495	1615	7230/8810			350/490	Z1-01-8
29.5-25	16/22	25.00/3.5	—	750	1875	12900/15000			250/325	Z1-01-8
16/70-24	10/14	13.00	—	410	1175	4750/5650			325/4.50	Z1-01-8



5.00-8 6.00-9 6.50-10 7.00-9 7.00-12 28X9-15 8.25-12 8.25-15

The drawing quality is good and the tyres are high in loading and good warmtherasing.

HS688

Industrial tyre / Forklift tyre	Tyre Size	Ply Rating	Rim		Inflated Dimensions		Max Load				Inflation Pressure	Valve Size
			Standard Rim	Permitted Rim	Section Width (mm)	Overall Diameter (mm)	10 km/h	25 km/h	40 km/h	50 km/h		
	5.00-8	8.10	3.50D	3.00D	137	470	950	765	665	595	800	TZ1-45
	6.00-9	10	4.00E	4.50E	160	540	1410	1135	985	885	850	TZ1-45
	6.50-10	10	5.00F	5.50F	175	590	1545	1245	1080	970	775	TZ1-45
	7.00-9	10	5.00S	-	190	590	1865	1500	1300	1170	850	TZ1-45
	7.00-12	12	5.00S	5.50S	190	676	2225	1790	1505	1400	850	TZ1-45
	28X9-15	12,14,16	7.0	7.00T	222	710	3515	2705	2180	1850	900	-
	8.25-12	12	6.5	5.00S	235	765	2950	2375	2060	1855	750	TZ1-50
	8.25-15	14	6.5	6.50T	235	840	3230	2600	2255	2030	800	TZ1-50



TECHNICAL FILE

TAITONG

SIZE	PR	PATTERN	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
6.50R16LT	12	HS268	4.50	110/105K	755	182	1060/925	670
7.00R16LT	14	HS268	5.50F	118/114K	778	202	1500/1320	770
7.50R16LT	14	HS206	6.00G	122/118L	802	210	1500/1320	770
7.50R16LT	14	HS268	6.00G	122/118L	802	210	1500/1320	770
7.50R16LT	14	HS918	6.00G	122/118L	802	210	1500/1320	770
8.25R16LT	16	HS268	6.50H	128/124K	860	230	1800/1600	770
8.25R16LT	16	HS918	6.50H	128/124K	860	230	1800/1600	770
8.25R20	16	HS268	6.50	139/137K	974	236	2430/2300	930
9.5R17.5	18	HS206	6.75	143/141M	842	240	2725/2575	930
9.5R17.5	18	HS928	6.75	143/141M	842	240	2725/2575	930
9.00R20	16	HS218	7.00	144/142K	1018	258	2800/2650	900
9.00R20	16	HS268	7.00	144/142K	1018	258	2800/2650	900
9.00R20	16	HS715K	7.00	144/142K	1018	258	2800/2650	900
10.00R20	18	HS218	7.50	149/146K	1052	275	3250/3000	930
10.00R20	18	HS268	7.50	149/146K	1052	275	3250/3000	930
10.00R20	18	HS715K	7.50	149/146K	1052	275	3250/3000	930
10.00R20	18	HS801Q	7.50	149/146K	1052	275	3250/3000	930
10.00R20	18	HS918+	7.50	149/146K	1052	275	3250/3000	930
10.00R20	18	HS978	7.50	149/146K	1052	275	3250/3000	930
11.00R20	18	HS218	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS258	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS259	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS268	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS715	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS716	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS725	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS735+	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS755+	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS801Q	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS918	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS938+	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS958+	8.00	152/149K	1082	286	3550/3250	930
11.00R20	18	HS968+	8.00	152/149K	1082	286	3550/3250	930
11R22.5	14	HS219	8.25	144/142M	1050	279	2800/2650	720
11R22.5	16	HS101	8.25	146/143M	1050	279	3000/2725	830
11R22.5	16	HS103	8.25	146/143M	1050	279	3000/2725	830
11R22.5	16	HS205	8.25	146/143M	1050	279	3000/2725	830
11R22.5	16	HS207	8.25	146/143M	1050	279	3000/2725	830
11R22.5	16	HS208	8.25	146/143M	1050	279	3000/2725	830
11R22.5	16	HS217	8.25	146/143M	1050	279	3000/2725	830
11R22.5	16	HS268	8.25	146/143M	1050	279	3000/2725	830
11R24.5	14	HS219	8.25	146/143M	1100	279	3000/2725	720
11R24.5	16	HS205	8.25	149/146L	1100	279	3250/3000	830
11R24.5	16	HS207	8.25	149/146L	1100	279	3250/3000	830
11R24.5	16	HS208	8.25	149/146L	1100	279	3250/3000	830
11R24.5	16	HS217	8.25	149/146L	1100	279	3250/3000	830
12.00R20	20	HS218	8.50	156/153K	1122	313	4000/3650	900
12.00R20	20	HS268	8.50	156/153K	1122	313	4000/3650	900
12.00R20	20	HS715	8.50	156/153K	1122	313	4000/3650	900
12.00R20	20	HS718	8.50	156/153K	1122	313	4000/3650	900
12.00R20	20	HS725	8.50	156/153K	1122	313	4000/3650	900

SIZE	PR	PATTERN	STANDARD RIM	LOAD INDEX & SPEED RATING	OUTER DIAMETER (mm)	SECTION WIDTH (mm)	MAX LOAD(KG) SINGLE/DUAL	MAX PRESSURE (KPA)
12.00R20	20	HS735+	8.50	156/153K	1122	313	4000/3650	900
12.00R20	20	HS755+	8.50	156/153K	1122	313	4000/3650	900
12.00R20	20	HS801Q	8.50	156/153K	1122	313	4000/3650	900
12.00R20	20	HS918	8.50	156/153K	1122	313	4000/3650	900
12.00R20	20	HS938+	8.50	156/153K	1122	313	4000/3650	900
12.00R20	20	HS958+	8.50	156/153K	1122	313	4000/3650	900
12.00R20	20	HS968+	8.50	156/153K	1122	313	4000/3650	900
12.00R24	20	HS108	8.50	160/157K	1226	313	4500/4125	900
12.00R24	20	HS18	8.50	160/157K	1226	313	4500/4125	900
12.00R24	20	HS216	8.50	160/157K	1226	313	4500/4125	900
12.00R24	20	HS218K	8.50	160/157K	1226	313	4500/4125	900
12.00R24	20	HS228	8.50	160/157K	1226	313	4500/4125	900
12.00R24	20	HS268	8.50	160/157K	1226	313	4500/4125	900
12.00R24	20	HS918	8.50	160/157K	1226	313	4500/4125	900
12R22.5	18	HS101	9.00	152/149M	1084	300	3550/3250	930
12R22.5	18	HS103	9.00	152/149M	1084	300	3550/3250	930
12R22.5	18	HS107	9.00	152/149M	1084	300	3550/3250	930
12R22.5	18	HS268	9.00	152/149M	1084	300	3550/3250	930
12R22.5	18	HS716	9.00	152/149K	1084	300	3550/3250	930
13R22.5	18	HS107	9.75	154/151L	1124	320	3750/3450	850
13R22.5	18	HS268	9.75	154/151L	1124	320	3750/3450	850
13R22.5	18	HS801Q	9.75	154/151L	1124	320	3750/3450	850
205/75R17.5	14	HS205	6.00	124/122M	753	205	1600/1500	750
215/75R17.5	16	HS205	6.00	126/124M	767	212	1700/1600	700
225/70R19.5	14	HS205	6.75	128/126M	811	226	1800/1700	760
235/75R17.5	16	HS205	6.75	132/130M	797	233	2000/1900	775
245/70R19.5	16	HS205	7.50	135/133M	833	248	2180/2060	830
255/70R22.5	16	HS205	7.50	140/137M	930	255	2500/2300	830
265/70R19.5	16	HS205	7.50	140/138M	867	262	2500/2360	775
275/70R22.5	16	HS205	8.25	148/145M	958	276	3150/2900	900
285/75R24.5	14	HS219	8.25	144/141L	1056	283	2800/2575	760
285/75R24.5	16	HS205	8.25	147/144L	1056	283	3075/2800	830
285/75R24.5	16	HS208	8.25	147/144L	1056	283	3075/2800	830
295/75R22.5	14	HS219	9.00	144/141L	1014	298	2800/2575	760
295/75R22.5	16	HS205	9.00	146/143L	1014	298	3000/2725	830
295/75R22.5	16	HS208	9.00	146/143L	1014	298	3000/2725	830
295/80R22.5	18	HS101	9.00	152/149M	1044	298	3550/3250	900
295/80R22.5	18	HS103	9.00	152/149M	1044	298	3550/3250	900
295/80R22.5	18	HS202	9.00	152/149M	1044	298	3550/3250	900
295/80R22.5	18	HS303	9.00	152/149M	1044	298	3550/3250	900
315/70R22.5	20	HS201	9.00	154/150M	1014	312	3750/3350	900
315/70R22.5	20	HS202	9.00	154/150M	1014	312	3750/3350	900
315/80R22.5	20	HS101	9.00	157/153L	1076	312	4125/3650	860
315/80R22.5	20	HS102	9.00	157/153L	1076	312	4125/3650	860
315/80R22.5	20	HS109	9.00	157/153L	1076	312	4125/3650	860
315/80R22.5	20	HS203	9.00	157/153L	1076	312	4125/3650	860
315/80R22.5	20	HS268	9.00	157/153L	1076	312	4125/3650	860
315/80R22.5	20	HS928	9.00	157/153L	1076	312	4125/3650	860
385/65R22.5	20	HS106	11.75	160K	1072	389	4500	900
385/65R22.5	20	HS166	11.75	160K	1072	389	4500	900
385/65R22.5	20	HS209	11.75	160K	1072	389	4500	900